

LAND CORNER RECORD

T. 1 N, R. 5 East, W.M. Skamania County
 Segregated Surveys: Corner Code No. A-1
 Name: n/a Corner No.: n/a
 DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

Originally set by Justin Chenoweth during 1856 G.L.O. survey of TIN. R4E.
 In May 1971, Dept of Game noted 2 B.T.'s. and a stone mound, and set a 1-1/4" pipe and cap which was not found during D.N.R. survey.

2. Description of Evidence Found:

58" live Fir B.T. with visible scribing at N 72 W, 85.8 ft.
 18" diameter mound of rock at N 82 W, 20.4 ft.
 50" live Fir B.T. at S 63 W, 269 ft.
 50" live Fir B.T. at S 63 E, 98.34 ft.

54
 M.G.K.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 607.07. Page No. 36. Date of work 22 July, '81.

Set standard D.N.R. iron pipe and stamped brass cap from intersection of 2 live Fir B.T.'s (NW & SE B.T.'s.)
 Shown on D.N.R. Final Map 441.
 See sketch on back.




Washington Plane Coordinates: South Zone, Y 104,813.42, X 1,552,659.72
 3rd Order Accuracy. Derived From: USC & GS 'Ells' and DNR 3-3N-4E

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date Sept. 27, 1983

Signature M. G. K. Certificate No. 11977



AUDITOR'S CERTIFICATE

Filed for record this 6th day of OCTOBER 1983 at 2:25 P.M. In Book V5 of MONUMENTS at page 19 at the request of Washington State Department of Natural Resources

J. M. Olson by J. Davis, rep.
 County Auditor

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.

G.L.O. 1857

Post

4" ALDER N 7 E 84 LKS
10" FIR N 78 W 130 LKS
6" FIR S 58 E 149 LKS
6" FIR S 63 W 408 LKS

Corner is trap station 402 - pg 33 this book

TOWNSHIP COR $\frac{36131}{116}$ T1-2N R4-5E

58" LIVE FIR BT W/VISIBLE SCRIBE

2 SCRIBED PAGES 1 20" INTO TREE

N 72 W 85.8 FT 1 2" INTO TREE

50" LIVE FIR BT DID NOT CHOP INTO

S 54 E 98.34 FT BT. TAG

50" LIVE FIR S 63 W 269' BT. TAG

Dept of Game survey, May 1971 notes 2 BT's
and pile of stone. They set 1 1/2" ppy/rq - we did not
find pipe, but pile of stones are 20.4 feet off gas
shown on sketch.

7-22-81

GORDON
BRESSLER
SPIELM

3.6

607.07

