

LAND CORNER RECORD

T 4 N, R 7E, W.M. County SKAMANIA
Segregated Surveys: Corner Code No. Z-17
Name: N/A Corner No.: N/A
DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration: ORIGINALLY SET BY G.L.O. SURVEYOR, JACOB RICHARDSON, DURING 1895 G.L.O. SURVEY. IN 1903, G.L.O. SURVEYOR, ROBERT F. WHITHAM, SET THE CLOSING CORNER FOR 3/2 T3N-R7E, 3.28 CHAINS EAST OF THIS CORNER. IN 1970, JOHN LAWSON, CEMENTED A D.N.R. BRASS CAP IN BEDROCK FROM 2 B.T.'S,

2. Description of Evidence Found: ABOVE DESCRIBED D.N.R. BRASS CAP CEMENTED IN BEDROCK.

2 B.T.'S
1-30" FIR STUB AT N 39° W - 39.5 FT.
1-34" FIR STUB AT S 38° W - 30.8 FT.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 600.24 Page No. 55 Date of work 10-18-83

SHOWN ON D.N.R. F.M. #477. SEE CORNER DIAGRAM ON REVERSE SIDE.



Registered

Washington Plane Coordinates: SOUTH Zone, Y 166292.23, X 1637688.53
3 RD. Order Accuracy. Derived From: LIES TO USC&GS "GREENLEAF"
& USC&GS "SEDUM POINT"
Pin Pointed on Photo No. _____ Date _____ Located at _____

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date December 1, 1983

Signature M. A. Kinnaman Certificate No. 11977



AUDITOR'S CERTIFICATE

Filed for record this 5 day of December 1983 at 1:40 P.M. In Book 4,7 of Monuments at page 77 at the request of

Dept. of Natural Resources
Gary M. Olson
County Auditor

GLO Survey of 1845 (Jacob Richardson)

80.00 Set post

10" Oak	N86E	40 L.	26.46
10" Fir	S60E	44 L.	29.04
36" Fir	S38W	50 L.	32.00
24" Fir	N37W	61 L.	40.26

In 1903, Robert Whitham set the C.C.
 32m 3.28 ch. east of this corner

S.C. 34/35 T4N R7E

Found DNR Brass cap cemented into
 bedrock by John Lawson in 1970,
 from 2 BT's.

96785

