

97319

## LAND CORNER RECORD

T. 3 N, R. 8E, W.M. Skamania County  
 Segregated Surveys: Corner Code No. A-3  
 Name: one-quarter corner Corner No.: 1/4  
 DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

## 1. History of Corner Establishment and Subsequent Restoration:

Established by Deputy Robert A Wheeler under contract No. 414 during Sept. 1896.  
 Set wood post.

Marked:

14" Fir N5W-13 lks..  
 16" Fir S12½W-13 lks..

## 2. Description of Evidence Found:

No evidence of the original corner or its accessories found.

## 3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 2 Page No. 2 Date of work 3/84

Set 2½"x30" Aluminum pipe with a 2½" Aluminum cap. Marked: PLS 16337  
 New Bearing Trees:  
 14" D-Fir S45W-36.4 ft. scribed XBT and with a 3/4" S6  
 Brass disk stamped PLS 16337. T3N R8E  
 9" D-Fir S2E-22.3 ft. scribed ¼S6BT and with a 3/4" 1984  
 Brass disk stamped PLS 16337.

Set guard post Southwest with decal survey marker only.  
 Nailed 54-4 and BT signs to BT's and painted band and blazes red.

Washington Plane Coordinates: Zone, Y, X  
 Order Accuracy. Derived From:  
 Pin Pointed on Photo No. Date Located at

## SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date MAR. 17, 1984

Signature Larry D. Bishop Certificate No. 16337

## AUDITOR'S CERTIFICATE

Filed for record this 23 day of MAR 1984 at 12:00 P.M. In Book 3/8 of Monuments at page 76 at the request of

