

LAND CORNER RECORD

T. 4 N, R. 7 1/2 E, W.M. Skamania County
Segregated Surveys: Corner Code No. Z-21
Name: Closing Corner Corner No.: S36
DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

Corner originally set by Deputy Alonzo Gesner under contract No. 571 during June and July 1901.

Set post.

Scribed 40" Fir S89E-91 s..

40" Fir N78E-9 lks..

2. Description of Evidence Found:

3/4" Iron pipe set by Olson and his R.P.'s.

Pipe is N88-56-41W-8.87 ft. from monument set.

Orig. 40" Fir now 24" D-Fir snag N87E-6.5 ft..

Orig. 40" Fir now 30" D-Fir snag S80E-61.5 ft..

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 3 Page No. 7 Date of work April 1984

Set 2 1/2" x 30" Aluminum pipe with a 2 1/2" Aluminum cap at intersection of Section lines.

New Bearing Trees:

10" D-Fir N68E-9.9 ft. scribed T4NR7 1/2 ES36BT and with a 3/4" Brass disk stamped PLS 16337.

14" D-Fir S43E-12.7 ft. scribed T3NR7 1/2 ES1BT and with a 3/4" Brass disk stamped PLS 16337.

Set guard posts South and East with decals 54-2 and survey marker.

Nailed 54-4 and BT signs to BT's and painted band and blazes red.

Marked: T4N
S36
R7E S36 CC
S1
R7 1/2
1984
T3N
PLS 16337

Washington Plane Coordinates: Zone, Y
Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date April 1984

Signature *Larry D. Bishop* Certificate No. 16337



AUDITOR'S CERTIFICATE

Filed for record this 23 rd day of MAY 1984 at 1:15 P.M. In Book 472 of RECORDS at page 16 at the request of

LARRY D. BISHOP

Alonzo Gesner County Auditor