LAND CORNER RECORD

This corner record correctly represents work performed by marker only. Set 20th x 30th Aluminum pipe with 22th Aluminum cap. Marked: 10th x 30th x	- h	Skamania	County	
Auditors certificate East one-quarter corner DLC. MES. Tract. Mining claim. Indian Albiment. Pederal Reserve. Townsite. History of Corner Establishment and Subsequent Restoration: Corner originally establishment and Subsequent Restoration: Seribed 10" dead Fir S15E-118 lk5 Seribed 10" dead Fir S15E-118 lk5 Seribed 10" dead Fir N51-30M-376 lks Description of Evidence Found: Orig. 20" Fir now 34" D-Fir N51/2M-346 lksface bored by Jlson to date blaze. R.P.'s per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. gram corner and indicate meridian and reference to map of record. Surveyor's Field Book 3. Page No. 4. Date of work April 1924 Set 23" x 30" Aluminum pipe wide 28" Aluminum cap. Marked: This 3. New Bearing Tree: 28" D-Fir 839-60.35 ft. scribed y 836BF and with a 3/4" Brass dick straped PIS 16537. Paced and scribed 3" partited kand and face red. Set guard post Morth of conner with decal survey marker only. Mailed 54-3 and 54-4 signs to BT. Washington Plane Coordinates: Order Accuracy. Derived From: Pin Pointed on Photo No. Date Located at SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter On. Located at 193 and 54-4 signs to BT. AUDITOR'S CERTIFICATE This corner record correctly represents who k performed by me or under my direction in compliance with the provisions of Chapter On. Located at 193 and 54-4 signs to BT. AUDITOR'S CERTIFICATE This corner record correctly represents who k performed by me or under my direction in compliance with the provisions of Chapter On. Located at 193 at 1.45 and 54-4 signs to BT. AUDITOR'S CERTIFICATE	Cerregated Surveyes			No. X-25
Discribe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. R.P. 's per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. R.P. 's per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. R.P. 's per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. R.P. 's per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. R.P. 's per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. R.P. 's per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Surveyor's Field Book 3. Page No. 4. Date of work April 1934 Rew Bearing Tree: 28th D-Fir 8594-60.35 ft. scribed (856BT and with a 374th Brass disk steaped PIS 16537). Pacced and soribed BP painted band and face red. Sot guard post North of corner with decal survey marker only. Sot guard post North of corner with decal survey marker only. Pin Pointed on Photo No. Date Located at SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 19, Laws of 1973. Date. April 19, 1984 Certificate No. AUDITOR'S CERTIFICATE AUDITOR'S CERTI	and the control of th	m e m		
History of Corner Establishment and Subsequent Restoration: Corner originally established by Deputy Alonzo Genere under contract No. 571 during June & July 1901 Set post. Scribed 10" dead Fir S15E-118 lks 10" Red Fir N51-30d-376 lks Description of Evidence Found: Orig. 20" Fir new 34" D-Fir R514d-346 lksface bored by Jlson to date blaze. R.P.'s per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. gram corner and indicate meridian and reference to map of record. Surveyor's Field Book 3. Page No 1. Date of work April 1904 Set 23th x 30" Aluminum pipe with 23" Aluminum cap. Harked: 28" D-Fir 8894-60.35 ft. scribed 18368T and with 3 3/4" Brass disk stamped PLS 1637 Paced and scribed 37 painted band and face red. Set guard post North of conner with decal survey marker only. Natiled 54-3 and 54-4 signs to BT. Washington Plane Coordinates: Order Accuracy. Derived From: Ein Pointed on Photo No. Date Located at SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or ander my direction in compliance with the provisions of Chapter 10, Laws of 1973. Date. April 19, 1984 AUDITOR'S CERTIFICATE This corner record this 23 SP. day of New York Certificate No. AUDITOR'S CERTIFICATE Filed for record this 23 SP. day of New York at page 21 at 1.45 C.M. 300k Y/7/2 AUDITOR'S CERTIFICATE	DLC, HES, Tract, Mi	ning Claim, Indian Allotme	Corne	r No.: E¼
Description of Evidence Found: Orig. 20" Fir now 34" D-Fir N5174-346 Iksface bored by Jison to date blaze. R.F.'s per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. R.F.'s per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. R.F.'s per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. R.F.'s per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. R.F.'s per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Surveyor's Field Book J. Page No. 4 Date of Work April 1984 New Bearing Tree: 28" D-Fir S894-60.35 ft. scribed /836BT and with a 3/4" Brass disk stamped PIS 16337. Paced and scribed 30 peinted band and face red. Set guard post Month of corner with decal survey marker only. Nailed 54-3 and 54-4 signs to ST. Washington Plane Coordinates: SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter on the provision of Chapter of the provision of Chapter On Laws of 1973. Data April 19, 1984 AUDITOR'S CERTIFICATE Filed for record this 23 ED day of Day of This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter On Laws of 1973. Data April 19, 1984 AUDITOR'S CERTIFICATE Filed for record this 23 ED day of Day of This corner record correctly represents work performed by me or 1973. Data April 19, 1984 AUDITOR'S CERTIFICATE Filed for record this 23 ED day of Day of This corner record correctly represents work performed by me or 1973. Data April 19, 1984 AUDITOR'S CERTIFICATE AUDITOR'S CERTIFICATE AUDITOR'S CERTIFICATE AUDITOR'S CERTIFICATE AUDITOR'S CERTIFICATE AUDITOR'S CERTIFICATE AUDITOR'S CERTIFICAT				
Description of Evidence Found: Orig. 20" Fir now 34" D-Fir N5174-346 Iksface bored by Jison to date blaze. R.F.'s per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. R.F.'s per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. R.F.'s per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. R.F.'s per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. R.F.'s per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Surveyor's Field Book J. Page No. 4 Date of Work April 1984 New Bearing Tree: 28" D-Fir S894-60.35 ft. scribed /836BT and with a 3/4" Brass disk stamped PIS 16337. Paced and scribed 30 peinted band and face red. Set guard post Month of corner with decal survey marker only. Nailed 54-3 and 54-4 signs to ST. Washington Plane Coordinates: SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter on the provision of Chapter of the provision of Chapter On Laws of 1973. Data April 19, 1984 AUDITOR'S CERTIFICATE Filed for record this 23 ED day of Day of This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter On Laws of 1973. Data April 19, 1984 AUDITOR'S CERTIFICATE Filed for record this 23 ED day of Day of This corner record correctly represents work performed by me or 1973. Data April 19, 1984 AUDITOR'S CERTIFICATE Filed for record this 23 ED day of Day of This corner record correctly represents work performed by me or 1973. Data April 19, 1984 AUDITOR'S CERTIFICATE AUDITOR'S CERTIFICATE AUDITOR'S CERTIFICATE AUDITOR'S CERTIFICATE AUDITOR'S CERTIFICATE AUDITOR'S CERTIFICATE AUDITOR'S CERTIFICAT	Corner originally established by	Subsequent Resto	oration:	
Described 10" dead Fir \$15E-118 lks 10" Red Fir N51-30W-376 lks Description of Evidence Found: Orig. 20" Fir now 34" D-Fir N51%W-346 lksface bored by Olson to date blaze. R.P.'s per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. R.P.'s per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. R.P. sper Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. R.P. sper Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. R.P. sper Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Surveyor's Field Book 3	Deputy Alonzo Gesner under contra	act No. 571 duri:	ng June & Ju	ly 1901
Description of Evidence Found: Orig. 20" Fir now 34" D-Fir N51/24-346 lksface bored by Olson to date blaze. R.P.'s per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. R.P.'s per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. J. Page No. 4 Date of work April 1984. Set 2½" x 30" Aluminum pipe with 2½" Aluminum sap. Marked: The Set 2½" x 30" Aluminum pipe with 2½" Aluminum sap. Marked: Per 12%" y 30" Aluminum pipe with 2½" Aluminum sap. Marked: Per 28" y 30" Aluminum pipe with 2½" Aluminum sap. Marked: Per 28" y 30" Aluminum pipe with 2½" Aluminum sap. Marked: Per 360 y 356 y 360 y	nec hose.			
Description of Evidence Found: Orig. 20" Fir now 34" D-Fir N51/M-346 lksface bored by Olson to date blaze. R.F.'s per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. gram corner and indicate meridian and reference to map of record. Surveyor's Field Book 3. Page No. 4 Date of work April 1984 Set 2½" x 30" Aluminum pipe with 2½" Aluminum cap. Marked: 3. Page No. 4 Stamped PLS 16337 New Bearing Tree: 28" D-Fir S894-60.55 ft. scribed '356BT and with 3. 3/4" Brass disk stamped PLS 16337 Faced and scribed 2D painted band and face red. PLS 16337 Faced and scribed 2D painted band and face red. Set guard post Nowth of corner with decal survey marker only. Nailed 54-3 and 54-4 signs to BT. Washington Plane Coordinates: Cone, Y Order Accuracy. Derived From: Washington Plane Coordinates: SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter on the complete of the provisions of Chapter on the complete of the provisions of Chapter on the complete of the provisions of Chapter on the provisions of Chapter of Mills 4111(1), 1984 AUDITOR'S CERTIFICATE Filed for record this 2.3 SD day of 10 the provisions of Chapter of Mills 4111(1), 1984 AUDITOR'S CERTIFICATE AUDITOR'S CERTIFICATE Signature AUDITOR'S CERTIFICATE AUDITOR'S CERTI	10" Red Fir N51-30W	-376 1ks		
Orig. 20" Fir now 34" D-Fir N511/41-346 Iksface bored by Jlson to date blaze. R.P.'s per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. gram corner and indicate meridian and reference to map of record. Surveyor's Field Book 3. Page No. 4 Date of work April 1934. Set 2½" x 30" Aluminum pipe with 2½" Aluminum cap. Marked: 28" D-Fir 8894-60.35 ft. scribed 15379. New Bearing Tree: 28" D-Fir 8894-60.35 ft. scribed 15379. Faced and scribed 3F painted band and face red. Set guard post North of corner with decal survey marker only. Nailed 54-5 and 54-4 signs to BT. Washington Plane Coordinates: Corner V. Corner V. Corner V. Corner V. Corder Accuracy. Derived From: Pin Pointed on Photo No. Date Located at SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter of the provisions of Chapter of the provision of 1973. Date. April 19, 1984 AUDITOR'S CERTIFICATE Filed for record this 23 80 day of 1993 at 1.45 c. M. AUDITOR'S CERTIFICATE Filed for record this 23 80 day of 1993 at 1.45 c. M. AUDITOR'S CERTIFICATE Filed for record this 23 80 day of 1993 at 1.45 c. M. AUDITOR'S CERTIFICATE Filed for record this 23 80 day of 1993 at 1.45 c. M. AUDITOR'S CERTIFICATE Filed for record this 23 80 day of 1993 at 1.45 c. M. AUDITOR'S CERTIFICATE Filed for record this 23 80 day of 1993 at 1.45 c. M. AUDITOR'S CERTIFICATE Filed for record this 23 80 day of 1993 at 1.45 c. M. AUDITOR'S CERTIFICATE Filed for record this 23 80 day of 1993 at 1.45 c. M. AUDITOR'S CERTIFICATE Filed for record this 23 80 day of 1993 at the request				
Orig. 20" Fir now 34" D-Fir N511/41-346 Iksface bored by Jlson to date blaze. R.P.'s per Olson. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. gram corner and indicate meridian and reference to map of record. Surveyor's Field Book 3. Page No. 4 Date of work April 1934. Set 2½" x 30" Aluminum pipe with 2½" Aluminum cap. Marked: 28" D-Fir 8894-60.35 ft. scribed 15379. New Bearing Tree: 28" D-Fir 8894-60.35 ft. scribed 15379. Faced and scribed 3F painted band and face red. Set guard post North of corner with decal survey marker only. Nailed 54-5 and 54-4 signs to BT. Washington Plane Coordinates: Corner V. Corner V. Corner V. Corner V. Corder Accuracy. Derived From: Pin Pointed on Photo No. Date Located at SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter of the provisions of Chapter of the provision of 1973. Date. April 19, 1984 AUDITOR'S CERTIFICATE Filed for record this 23 80 day of 1993 at 1.45 c. M. AUDITOR'S CERTIFICATE Filed for record this 23 80 day of 1993 at 1.45 c. M. AUDITOR'S CERTIFICATE Filed for record this 23 80 day of 1993 at 1.45 c. M. AUDITOR'S CERTIFICATE Filed for record this 23 80 day of 1993 at 1.45 c. M. AUDITOR'S CERTIFICATE Filed for record this 23 80 day of 1993 at 1.45 c. M. AUDITOR'S CERTIFICATE Filed for record this 23 80 day of 1993 at 1.45 c. M. AUDITOR'S CERTIFICATE Filed for record this 23 80 day of 1993 at 1.45 c. M. AUDITOR'S CERTIFICATE Filed for record this 23 80 day of 1993 at 1.45 c. M. AUDITOR'S CERTIFICATE Filed for record this 23 80 day of 1993 at the request	r <u>end</u> a de la Carta de Carta d			
Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. gram corner and indicate meridian and reference to map of record. Surveyor's Field Book Page No. 4 Date of work April 1984 Set 250 x 300 Aluminum pipe with 250 Aluminum cap. Marked: The Set 250 x 300 Aluminum pipe with 250 Alumi	Description of Evidence Found:			
Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. gram corner and indicate meridian and reference to map of record. Surveyor's Field Book 3	Orig. 20" Fir now 34" D-Fir N51%	√-346 lksface t	ored by Also	on to date blace
Page No. 4 Date of work April 1984 Set 2½" x 30" Aluminum pipe with 2½" Aluminum cap. Marked: The Set 1984 Aluminum pipe with 2½" Aluminum cap. Marked: The Set 28" D-Fir 889%-60.55 ft. scribed / 836BT and with a 3/4" Brass disk stamped PLS 16337. Faced and scribed BT painted band and face red. Set guard post North of corner with decal survey marker only. Nailed 54-5 and 54-4 signs to BT. Washington Plane Coordinates: Zone, Y. Order Accuracy. Derived From: Pin Pointed on Photo No. Date Located at SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date. April 19, 1984 Signature Course of this 23.80 day of 1974 at 1870 August 1875 Certificate No. AUDITOR'S CERTIFICATE Filed for record this 23.80 day of 1970 at 1870 August 1875 at page 2 at 1.45 Sook 1972 Of 1970 August 1875 at page 2 at 1.45 Sook 1972 August 1850 August 1875 Augus	R.P.'s per Olson.		0100	n to date braze.
Page No. 4 Date of work April 1984 Set 2½" x 30" Aluminum pipe with 2½" Aluminum cap. Marked: The Set 1984 Aluminum pipe with 2½" Aluminum cap. Marked: The Set 28" D-Fir 889%-60.55 ft. scribed / 836BT and with a 3/4" Brass disk stamped PLS 16337. Faced and scribed BT painted band and face red. Set guard post North of corner with decal survey marker only. Nailed 54-5 and 54-4 signs to BT. Washington Plane Coordinates: Zone, Y. Order Accuracy. Derived From: Pin Pointed on Photo No. Date Located at SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date. April 19, 1984 Signature Course of this 23.80 day of 1974 at 1870 August 1875 Certificate No. AUDITOR'S CERTIFICATE Filed for record this 23.80 day of 1970 at 1870 August 1875 at page 2 at 1.45 Sook 1972 Of 1970 August 1875 at page 2 at 1.45 Sook 1972 August 1850 August 1875 Augus			•	" / P
Page No. 4 Date of work April 1984 Set 2½" x 30" Aluminum pipe with 2½" Aluminum cap. Marked: The Set 1984 Aluminum pipe with 2½" Aluminum cap. Marked: The Set 28" D-Fir 889%-60.55 ft. scribed / 836BT and with a 3/4" Brass disk stamped PLS 16337. Faced and scribed BT painted band and face red. Set guard post North of corner with decal survey marker only. Nailed 54-5 and 54-4 signs to BT. Washington Plane Coordinates: Zone, Y. Order Accuracy. Derived From: Pin Pointed on Photo No. Date Located at SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date. April 19, 1984 Signature Course of this 23.80 day of 1974 at 1870 August 1875 Certificate No. AUDITOR'S CERTIFICATE Filed for record this 23.80 day of 1970 at 1870 August 1875 at page 2 at 1.45 Sook 1972 Of 1970 August 1875 at page 2 at 1.45 Sook 1972 August 1850 August 1875 Augus				
Page No. 4 Date of work April 1984 Set 2½" x 30" Aluminum pipe with 2½" Aluminum cap. Marked: The Set 1984 Aluminum pipe with 2½" Aluminum cap. Marked: The Set 28" D-Fir 889%-60.55 ft. scribed / 836BT and with a 3/4" Brass disk stamped PLS 16337. Faced and scribed BT painted band and face red. Set guard post North of corner with decal survey marker only. Nailed 54-5 and 54-4 signs to BT. Washington Plane Coordinates: Zone, Y. Order Accuracy. Derived From: Pin Pointed on Photo No. Date Located at SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date. April 19, 1984 Signature Course of this 23.80 day of 1974 at 1870 August 1875 Certificate No. AUDITOR'S CERTIFICATE Filed for record this 23.80 day of 1970 at 1870 August 1875 at page 2 at 1.45 Sook 1972 Of 1970 August 1875 at page 2 at 1.45 Sook 1972 August 1850 August 1875 Augus			_ \	
Page No. 4 Date of work April 1984 Set 2½" x 30" Aluminum pipe with 2½" Aluminum cap. Marked: The Set 1984 Aluminum pipe with 2½" Aluminum cap. Marked: The Set 28" D-Fir 889%-60.55 ft. scribed / 836BT and with a 3/4" Brass disk stamped PLS 16337. Faced and scribed BT painted band and face red. Set guard post North of corner with decal survey marker only. Nailed 54-5 and 54-4 signs to BT. Washington Plane Coordinates: Zone, Y. Order Accuracy. Derived From: Pin Pointed on Photo No. Date Located at SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date. April 19, 1984 Signature Course of this 23.80 day of 1974 at 1870 August 1875 Certificate No. AUDITOR'S CERTIFICATE Filed for record this 23.80 day of 1970 at 1870 August 1875 at page 2 at 1.45 Sook 1972 Of 1970 August 1875 at page 2 at 1.45 Sook 1972 August 1850 August 1875 Augus		- 49		
Page No. 4 Date of work April 1984 Set 2½" x 30" Aluminum pipe with 2½" Aluminum cap. Marked: The Set 2½" x 30" Aluminum pipe with 2½" Aluminum cap. Marked: The Set 2½" x 30" Aluminum pipe with 2½" Aluminum cap. Marked: The Set 28" D-Fir 889%-60.35 ft. scribed / 836BT and with a 3/4" Brass disk stamped PLS 16337. Faced and scribed BT painted band and face red. Set guard post North of corner with decal survey marker only. Nailed 54-5 and 54-4 signs to BT. Washington Plane Coordinates: Zone, Y. Order Accuracy. Derived From: Pin Pointed on Photo No. Date Located at SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter of the Set 23 Set 25 Set		. 6 . 6.	\]	
Page No. 4 Date of work April 1984 Set 2½" x 30" Aluminum pipe with 2½" Aluminum cap. Marked: The Set 2½" x 30" Aluminum pipe with 2½" Aluminum cap. Marked: The Set 2½" x 30" Aluminum pipe with 2½" Aluminum cap. Marked: The Set 2½" x 30" Aluminum pipe with 2½" Aluminum cap. Marked: The Set 2½" x 30" Aluminum pipe with 2½" Aluminum cap. Marked: The Set 2½" x 30" Aluminum pipe with 2½" Aluminum cap. Marked: The Set 2½" x 30" Aluminum cap. Marked: The Set 3½" x 30" Aluminum cap. Marked: The Set 2½" x 30" Aluminum cap. Marked: The Set 3½" x 30" Aluminum cap. Mark	Describe Monument, Accessories and	Corollary Data to	Pornetuete 4h	:- A
Set 2½" x 30" Aluminum pipe with 2½" Aluminum cap. Marked: T4N ½ New Bearing Tree: \$36 28" D-Fir \$89\-60.35 ft. scribed \(\) \$36\BT and with a 3/\psi Brass disk stamped PLS 16337. Paced and scribed BT painted band and face red. PLS 16337 Set guard post North of corner with decal survey marker only. Nailed 54-5 and 54-4 signs to BT. Washington Plane Coordinates: Zone, Y	o maicate inclinial a	illi teletelle to mai	n of rooped C	urveyor's Field Book I
New Bearing Tree: 28" D-Fir \$89%-60.35 ft. scribed \$836BT and with 3 3/4" Brass disk stamped PLS 16337. Faced and scribed BT painted band and face red. Set guard post North of corner with decal survey marker only. Nailed 54-3 and 54-4 signs to BT. Washington Plane Coordinates: Order Accuracy. Derived From: Pin Pointed on Photo No. Date Located at SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 10, Laws of 1973. Date. April 19, 1984 Signature AUDITOR'S CERTIFICATE Certificate No. AUDITOR'S CERTIFICATE Signature AUDITOR'S CERTIFICATE Cook. "/7/2" of Missian Market No. 19.54 at 1.45 e.M. Sook. "/7/2" at the request of	Set 2½" x 30" Aluminum pipe with	26! Aluminum can	Manisod.	mbar at
28" D-Fir \$89%-60.35 ft. scribed y \$36BT and with a 3/4" Brass disk stamped PLS 16337. Faced and scribed BT painted band and face red. Set guard post North of corner with decal survey marker only. Nailed 54-5 and 54-4 signs to BT. Washington Plane Coordinates: Order Accuracy. Derived From: Pin Pointed on Photo No. Date Located at SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 10, Laws of 1973. Date. April 19, 1984 16537 Certificate No. AUDITOR'S CERTIFICATE Filed for record this 23 SP day of 10/32 19.5% at 1.45 2.M. Sook. "/7/2 of 10/340/16715 at page 21 at the request of		7 Intelligence Cap	• Harkeu:	
Washington Plane Coordinates: Very Corder Accuracy. Derived From: Pin Pointed on Photo No. Date Surveyor's Certificate This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter of Control o	28" D-Fir S89W-60.35 ft. scrib	ed 1/S36BT and wit	th R7½	9
Washington Plane Coordinates: Order Accuracy. Derived From: Pin Pointed on Photo No. Date Surveyor's Certificate This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date April 19, 1984 Signature AUDITOR'S CERTIFICATE Filed for record this 23 SD day of 1000 MININGS at page 21 at the request of 1980 MININGS at page 21 at the request of			All I	
Washington Plane Coordinates: Zone, Y , X Order Accuracy. Derived From: Pin Pointed on Photo No. Date Located at SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date. April 19, 1984 Signature 16327 Certificate No. AUDITOR'S CERTIFICATE Gay of MAN AUDITOR'S CERTIFICATE AUDITOR'S CERTI	set guard post North of corner wi-	and lace red. th decal survey r	marker only	ועלסו מדו
SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date April 19, 1984 Signature AUDITOR'S CERTIFICATE Filed for record this 23 80 day of 1000 at 10	Nailed 54-3 and 54-4 signs to BT.	an document Survey in	marker Unity.	-50023212E
SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date April 19, 1984 Signature AUDITOR'S CERTIFICATE Filed for record this 23 80 day of 1000 at 10				The Court,
SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date April 19, 1984 Signature AUDITOR'S CERTIFICATE Filed for record this 23 80 day of 1000 at 10		~ \		
SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date April 19, 1984 Signature AUDITOR'S CERTIFICATE Filed for record this 23 80 day of 1000 at 10				<u>(f</u>
SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or inder my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date April 19, 1984 Signature AUDITOR'S CERTIFICATE Filed for record this 23 80 day of 1000 at 10		4		
SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or inder my direction in compliance with the provisions of Chapter io, Laws of 1973. Date April 19, 1984 Signature AUDITOR'S CERTIFICATE Filed for record this 23 80 day of 1000 at 10				Ţ.
SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or ander my direction in compliance with the provisions of Chapter (a), Laws of 1973. Date April 19, 1984 Signature AUDITOR'S CERTIFICATE Filed for record this 23 SP day of 1000 at 1			5	
SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or ander my direction in compliance with the provisions of Chapter (a), Laws of 1973. Date April 19, 1984 Signature AUDITOR'S CERTIFICATE Filed for record this 23 SP day of 1000 at 1	Washington Plane Coordinates:	Zone V		5000
SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 10, Laws of 1973. Date April 19, 1984 Signature AUDITOR'S CERTIFICATE Siled for record this 23 80 day of 10 8/3 (Certificate No.) AUDITOR'S CERTIFICATE Siled for record this 23 80 day of 10 8/3 (Certificate No.) AUDITOR'S CERTIFICATE Siled for record this 23 80 day of 10 8/3 (Certificate No.) AUDITOR'S CERTIFICATE Siled for record this 23 80 day of 10 8/3 (Certificate No.) AUDITOR'S CERTIFICATE Siled for record this 23 80 day of 10 8/3 (Certificate No.) AUDITOR'S CERTIFICATE Siled for record this 23 80 day of 10 8/3 (Certificate No.) AUDITOR'S CERTIFICATE Siled for record this 23 80 day of 10 8/3 (Certificate No.) AUDITOR'S CERTIFICATE Siled for record this 23 80 day of 10 8/3 (Certificate No.) AUDITOR'S CERTIFICATE Siled for record this 23 80 day of 10 8/3 (Certificate No.) AUDITOR'S CERTIFICATE Siled for record this 23 80 day of 10 8/3 (Certificate No.) AUDITOR'S CERTIFICATE Siled for record this 23 80 day of 10 8/3 (Certificate No.) AUDITOR'S CERTIFICATE Siled for record this 23 80 day of 10 8/3 (Certificate No.)	Order Accuracy. Derived	From:		, А
SURVEYOR'S CERTIFICATE This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 10, Laws of 1973. Date April 19, 1984 Signature AUDITOR'S CERTIFICATE Tiled for record this 23.80 day of 1000 at 1	Pin Pointed on Photo No. Date	e Yo	antad at	
AUDITOR'S CERTIFICATE Signature AUDITO			cated at	
AUDITOR'S CERTIFICATE Signature AUDITOR'S CERTIFICATE AUDITOR'S CERTIFICATE AUDITOR'S CERTIFICATE Signature AUDITOR'S CERTIFICATE AUDITOR'S CER				[Sraple
AUDITOR'S CERTIFICATE Signature AUDITOR'S CERTIFICATE A	This corner record correctly represents	s work performed	by me or	GRY D. B/O
AUDITOR'S CERTIFICATE Filed for record this 23 RP day of 10 RM 1984 at 1.45 P.M. Book 4/7/2 of 10 RM 1984 at 1.45 P.M. 19 RM 19 RM 19 RM 1984 at 1.45 P.M. 19 RM 19	muci my unrection in compliance with	h tha mmani-i	. ~ .	THE OWN STRANGE
AUDITOR'S CERTIFICATE Siled for record this 23 RP day of 1) RM 1984 at 1.45 P.M. Book 4/7/2 of MENDINGENTS at page 21 at the request of	ignature & Birling	163	37	1 ((E) S
Filed for record this 23 RD day of DIMY 1989 at 1.45 P.M. Book 4/772 of MORAUNENTS at page 21 at the request of		Certific	ate No.	12/1
Filed for record this 23 RD day of DIMY 1989 at 1.45 P.M. Book 4/772 of MOSMONIANTS at page 21 at the request of				Fr. Treate Land
Filed for record this 23 RP day of 10 May 1989 at 1.45 P.M. Book 4/7/2 of 10 May 10 11 11 11 11 at the request of 10 May D B15000	AUDIT	OR'S CERTIFICAT	'E	OFFILI I AND STIME
1988 D BISHOP at page 21 at the request of	Filed for record this 23 RD day of	DIGA	19.59 at	1.45 P.M.
1/1/11/1	LARKY D BISHOP	allillings at p	age 21 a	t the request of
sell Obor of of law Day	№	3/1 1/1.1	100	1 1

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.