

LAND CORNER RECORD

T 4 N, R 9E, W.M. Skamania County
 Segregated Surveys: Corner Code No. N-17
 Name: Section Corner Corner No.:
 D.L.C., D.E.S., Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

The corner was originally set by Deputy Jacob Richardson during Oct./Nov. 1892 under contract No. 383.

Set post:

Scribed 10" Cedar N71E-68 lks..
 12" Hemlock S58E-33 lks..
 8" Cedar S70W-35 lks..
 10" Cedar N34W-61 lks..

2. Description of Evidence Found:

DNR 3" Brass cap set in concrete post-DNR location tags on WRC stump and two D-Fir rep.'s.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location:

gram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 3 Page No. 9 Date of work July 1984

New Bearing Trees:

12" D-Fir N24W-34.5 ft. scribed T4NR9ES15BT
 and with a 3/4" Brass disk stamped PLS 16336.
 17" D-Fir N18E-59.3 ft. scribed T4NR9ES14BT
 and with 3/4" Brass disk stamped PLS 16337.
 10" Alder S53W-13.8 ft. scribed T4NR9ES22BT (Alder bark scribed)
 and with a 3/4" Brass disk stamped PLS 16337.
 11" Alder S25E-19.3 ft. scribed T4NR9ES23BT (Alder bark scribed)
 and with 3/4" Brass dis: stamped PLS 16337.

Set guard posts North and West with 54-2a and survey marker decals.
 Nailed 54-4 and 54-3 signs to BT's and painted bands and blazes red.

Washington Plane Coordinates: Zone, Y, X
 Order Accuracy. Derived From:
 Pin Pointed on Photo No. Date Located at.

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date July 1984

Signature

16337

Certificate No.



AUDITOR'S CERTIFICATE

Filed for record this 24th day of July 1984 at 12:20 P.M. In Book 4/9 of RECORDS at page 56 at the request of

BISHOP SURVEYING, INC.

W. M. Olson by A. News, Dep.

County Auditor