## LAND CORNER RECORD

Skamanla

County

T 4 N, R , W.M. Corner Code No. M-14

Segregated Surveys:

Southwest one-sisteenth corner

Corner No.:

DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

Name:

2. Description of Evidence Found:

Iron rod S43-26-26W-18.39 feet.



3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location, Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No.

Page No.

Date of work June 1934

Set 25 x 30" Aluminum pipe with a 25 Aluminum cap. New Bearing Trees:

T4N R9E Marked: \$15 \$\mathbb{S} 1/16

11" D-Fir N48W-21.3 ft. scribed SW1/16S15BT and with a 3/4" Brass disk stamped PLS 16337.

13" D-Fir N19E-12.7 ft. scribed SW1/16S15BT and

1984 PLS 16337

with a 3/4" Brass disk stamped PLS 16337. Set guard posts lest and South with 54-2a and survey

marker decals.

Nailed 54-9 and 54-3 signs to BT's and painted bands and blazes red.

Zone, Y. Washington Plane Coordinates: Order Accuracy. Derived From: Located at. ... Date Pin Pointed on Photo No.

## SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date July 1984 16337

Signature Certificate No.

AUDITOR'S CERTIFICATE

Filed for record this 241H day of Book 4/9 of Oi ILLLY of MONUMENTS \_at page 59

1984 at 12:35

BISHOP SURVEYING, INC.

at the request of.

[SEAL]

Ounts Additor 1 Juin 1 Beg.

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 19\_\_\_\_,