

LAND CORNER RECORD

T 3 N, R 7 East, W.M. Skamania County
Segregated Surveys: Corner Code No. A-25
Name: Recinds L.C.R. #87583 dated 14 November 1978 Corner No.: n/a
DLC, RRS, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:


Originally set by G.L.O. surveyor, Jacob Richardson, during 1895 G.L.O. survey.
During 1903 G.L.O. Retracement survey this corner was found and reestablished by Robert F. Whitham
In 1978, the Dept. of Natural Resources set a D.N.R. concrete monument at calculated corner position.

2. Description of Evidence Found:

Above described D.N.R. concrete monument with stamped brass cap.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 600.12 Page No. 37 Date of work 9-26-'84

Reset found D.N.R. concrete monument to newly calculated modified single proportion corner position. Date restamped on brass cap '1984'.
Shown on D.N.R. Final Map # 315.
See corner diagram on reverse side.



Washington Plane Coordinates: South Zone, Y 166,009.14 X 1,648,094.37
3rd Order Accuracy. Derived From: Ties to USC & GS Control Stations
'Greenleaf' and 'Sedum Point'.

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date JAN 15, 1985

Signature M. A. Kinnaman Certificate No. 11977



AUDITOR'S CERTIFICATE

Filed for record this 21 day of JANUARY 1985 at 11:50 A.M. In
Book 37 of MONUMENTS at page 25 at the request of
Washington State Department of Natural Resources

J. M. Nelson County Auditor

GLO Survey of 1895

North 80.00 Set fir post

12" fir N48W 107L

6" fir S82°30'W 175L

1901 Resurvey of 2nd Guide Meridian

North 78.31 found corner

1903 Retacement of 2nd Guide Meridian

North 79.61 corner bears E, 40 links distance.

Post & BT's burned down. Set a fir

post, raised mound of stone around post, 30" base, 20" high

Township Corner $\frac{36}{1}$ T4N T3N R7E, W.M.

Found no original evidence

9-26-84

Gordon
Breider

37
600.12

