

# LAND CORNER RECORD

T 6 N, R 6E, W.M. Skamania County  
Segregated Surveys: Corner Code No. J-3

Name: \_\_\_\_\_ Corner No.: \_\_\_\_\_  
DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:  
Corner set by Chester W. Peckie in 1921. Set iron post, 3 ft long, 1" diam,  
25 in. in ground, with brass cap marked  
A 14" for line N42°W, 44 lks, mkt 1/4 S1E B1.  
A 10" for line S65E, 7 lks, mkt 1/4 S1E B1.

1 57  
4 518  
1921

2. Description of Evidence Found:  
A 2" brass cap on 1" iron pipe in good condition mkt:

1 57  
4 518  
1921


3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 3 Page No. 15 Date of work 11/6/84

Set reference 6.11.11.11  
A 8" Douglas fir S54°E, 29.24 ft, mkt 1/4 S1E B1  
A 3/4" x 30" rubber 1" diam cap has N 19°W, 10.16 ft mkt 76NR06  
KM 11-17  
LS1E734

BT and Attention signs on BT and brass cap "LS1E734".  
Concrete post with BT and Attention signs attached adjacent to ref. mon.  
Concrete post with Attention sign adjacent to 1921 iron


Washington Plane Coordinates: \_\_\_\_\_ Zone, Y \_\_\_\_\_, X \_\_\_\_\_  
Order Accuracy. Derived From: \_\_\_\_\_

Pin Pointed on Photo No. \_\_\_\_\_ Date \_\_\_\_\_ Located at \_\_\_\_\_



### SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date 1/31/85  
Beulah L. Jones Signature 18734 Certificate No.



### AUDITOR'S CERTIFICATE

Filed for record this 21 day of JANUARY 1985 at 12:22 P.M. In Book 6/6 of PROVIDENTIALS at page 21 at the request of 1. S. Frost  
William J. New County Auditor