

LAND CORNER RECORD

T 6 N, R 6 E, W.M. Skamania County
 Segregated Surveys: Corner Code No. 2-1
 Name: Corner No.:
 D.L.C. RES. Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

Corner set by C. Frank Rhodes in 1909. Set under the boulder
 15 x 12 x 6 in., 10 in. in ground, with 1/4 in West face, from which bears:
 A for 30 in diam S 13 E, 28 ft. with 1/4 S 13 E.
 A for 38 in diam N 64 W, 25 ft. with 1/4 S 13 E.

2. Description of Evidence Found:

Barnett stone 6" x 4", 6" above ground firmly set, marked 1/4 on
 West face.
 A 36" clay bar N 64 W, 16.2 ft., No mark visible.
 A 46" clay bar S 13 E, 19.2 ft., no marks visible.

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Dia- gram corner and indicate meridian and reference to map of record. Surveyor's Field Book No.

3 Page No. 14 Date of work 11/5/84
 Set L&S - 1 inch above men, 18" deep with stone and earth. Placed
 original stone under men. Placed mound of stone around men.

A 12' clay bar N 42 E, 45.82 ft. with 1/4 S 13 E.

Cap marked
 TAN
 R 45 1/4 R 66
 S 13 1/2 E
 1984
 L 518734

A 6" hummock N 74 W, 19.48 ft. with X B.

BT and Attention signs and brass tag, "L 518734" on
 each BT.

Corrovide post with Attention sign adjacent to men.

Washington Plane Coordinates: Zone, Y, X

Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or
 under my direction in compliance with the provisions of Chapter
 50, Laws of 1973. Date 1/31/85

Signature

Certificate No. 98899

AUDITOR'S CERTIFICATE

Filed for record this 5th day of FEBRUARY 1985 at 12:45 PM. In
 Book 6/6 of MINIMUM IS at page 23 at the request of

County Auditor

