LAWSON LAND SURVEYING

(206) 256-8008

JOHN G. LAWSON Registered Professional Land Surveyor Registered Professional Linguister

Name:

Found:

HE5 #232, Corner #2

Y Piaza 14612 A 4th Plain Rd Vancouver WA 98662 LAND CORNLR RECORD

T 4 N, R 7E , W.M.; Skamania County

Corner Code Number: ______Page 1 of 1

Corner Number

DLC, HES Mining Claim, Indian Allotment, Federal Reserve, Townsite

1. History of Corner Establishment and Subsequent Restoration; description of Evidence

This corner was set by Frederick W. Rase during survey in May, 1916. He drove an iron wedge into the center of a Douglas Fir stump 40" in diameter for the corner, raised a mound of stone within the claim, and scribed a Fir 18" in diameter North 69° West, 106 links.

We found a mound of stones and old bent 1" iron bar lying on the ground near it. 01d 40" Fir stump was found, but no sign of iron wedge or 18" B.T.



LAWSON LAND SURVEYING Job # 34 -83 - 260 We set a }" Iron Rod with Lawson #11989		The second secon	
stump for the corner. We then set a 23" of the mound of stone for witness corner	aluminum pipe in	the center t as follow:	TUN R7E WAY
North 49° West, 9.9 feet to a railroad sp Douglas Fir scribed WC RP with meta		of a 14"	WITNESS COR. HES. NO 232
South 24° East, 9.9 feet to a railroad sp Bouglas Fir, scribed WC RP with meta		of in 8"	(LENO. 2
Washington Plane Coordinates:	Zone, Y		
Order of Accuracy. Deri	ved trom:		
Pin Pointed on Photo No. Date	l oc	ited at	

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973.

Signature Date June 81

Certificate Number 11989

Registered S Indexed, pir S Indirect Sumed Indially

99396
AUDITOR'S CERTIFICATE

Filed for record	this 17M day o	f <u>June</u>	_, 19 <u>6</u> 5 at	21.50 P.M.
In book 4/7	of MONUMENTS	<u>s</u> at Page _	98	at the request
of	JOHN LAWSON		£	

MM Olbon by d. Dep County Auditor