

RES 20-1808(9-77)

LAND CORNER RECORD

SKAMANIA County
T. 7 N, R. 5E, W.M. Corner Code No. 0-7
Aggregated Surveys:
Name: Center North 1/16 Section 20 Corner No.: C-N 1/16 S20
DLC, H&B, Tract, Mining Claim, Ladder, Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

NONE

2. Description of Evidence Found:

NONE

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. 259-C Page No. 22 Date of work 8-9-84

6" HEMLOCK
BT
SCRIBED
"C-N 1/16 S20 BT"

20.95 FT.
N 01° 12' W

S 59° E
12.14 FT.

BT HEMLOCK
BT
SCRIBED
"C-N 1/16 S20 BT"

Set a 2 1/2" x 30" Aluminum Pipe, 26" in the ground with an aluminum cap. No stones available within 250' for stone mound. Cleared a 12' circle around monument.

Painted a 6" orange band around all BT's and painted faces.

Set a 6' fibreglass guard post w/54-9 sign North 3.0' on line.

Attached USFS 54-3 and 54-9 signs on all BT's

Nailed brass survey washers 1S 20898 in the top circle of newly scribed "B"'s and also at point of measurement on side of trees.

No
Scale

Washington Plane Coordinates: Zone, Y
Order Accuracy. Derived From:

Pin Pointed on Photo No. Date Located at

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or under my direction in compliance with the provisions of Chapter 50, Laws of 1973. Date August 10, 1984

Signature

Certificate No. 20898



AUDITOR'S CERTIFICATE

Filed for record this 23RD day of AUGUST 1985 at 11:15 A.M. In Book 7/5 of MONUMENTS at page 64 at the request of BUTLER & ZENKNER LAND SURVEYORS, INC.

Registered s

Indexed, Sir

Indirect

Filmed

Mailed

Form prescribed by Bureau of Surveys and Maps pursuant to the provisions of Section 5 (2), Chapter 50, Laws of 1973.