

OF THE QUARTER POST BETWEEN SECTIONS 10 AND 11, THENCE WESTERLY AND AT RIGHT ANGLES WITH SAID WESTERLY LINE OF SAID BRADFORD D.L.C. 500 FEET, THENCE SOUTHEASTERLY PARALLEL WITH THE WESTERLY LINE OF SAID D.L.C. 1500 FEET, THENCE EAST 700 FEET, MORE OR LESS TO THE WESTERLY LINE OF SAID D.L.C. IN SECTION 14, THENCE NORTH ON SAID WESTERLY LINE OF SAID D.L.C. TO THE SECTION LINE BETWEEN SECTIONS 11 AND 14 THENCE WEST ON SAID SECTION LINE TO THE WESTERLY LINE OF SAID CLAIM IN SECTION 11 AND THENCE NORTHWESTERLY ALONG SAID WESTERLY LINE OF SAID CLAIM 1300 FEET, MORE OR LESS TO THE PLACE OF BEGINNING.

III.

TO GEO. M. SCAMMON.

BEGINNING AT QUARTER CORNER ON NORTH LINE OF SECTION 22 BEING THE NORTHEAST CORNER OF LOT 2; THENCE SOUTH 660 FEET; THENCE WEST 660 FEET; THENCE SOUTH 540 FEET TO THE NORTH BOUNDARY OF THE STATE HIGHWAY RIGHT OF WAY; THENCE WESTERLY ALONG SAID BOUNDARY TO A POINT 40 FEET WEST OF THE WEST LINE OF LOT 2; THENCE NORTH TO A POINT 40 FEET WEST OF THE NORTHWEST CORNER OF LOT 2, THENCE EAST ALONG NORTH LINE OF SECTION 22 1360 FEET TO THE NORTHEAST CORNER OF LOT 2 TO THE PLACE OF BEGINNING CONTAINING 30 ACRES, MORE OR LESS, ALL IN TOWNSHIP 2 NORTH, RANGE 7 EAST OF WIL. MER.

ALSO A PERPETUAL RIGHT OF WAY FOR AND TO RIGHT TO LAY A LINE OF PIPE NOT TO EXCEED 6 INCHES IN DIAMETER BY THE MOST PRACTICAL AND SHORTEST ROUTE OVER AND ACROSS LANDS OF THE GRANTOR TO A CERTAIN SPRINGS LOCATED 306 FEET SOUTH MORE OR LESS OF THE NORTHEAST CORNER OF THE NORTH WEST QUARTER OF SOUTHWEST QUARTER OF SECTION 15, TOWNSHIP 2, NORTH OF RANGE 7, EAST OF W.M. WITH PERPETUAL RIGHT FOR INGRESS AND EGRESS FOR LAYING, REPAIRING AND MAINTAINING SAID PIPE LINE AND THE RIGHT TO DO SUCH WORK AND IMPROVEMENTS AS MAY BE NECESSARY AT THE SPRING FOR THE SUCCESSFUL TAKING OF THE WATER THEREFROM BY MEANS OF SAID PIPE LINE. "R"-157.

IV.

TO GEO. CHRISTENSON.

COMMENCING AT THE NORTHWEST CORNER OF THE B. BISHOP D.L.C. 39, A STONE 6X8X12 INCHES, MARKED C39 BEARING TREES STANDING; THENCE SOUTH ON WEST LINE OF CLAIM AT 1364 FT. THE NORTHEAST CORNER OF THE G. W. JOHNSON D.L.C. AT 1860 FEET INTERSECT THE NORTH EDGE OF THE GREENLEAF SLOUGH, SET POST; THENCE ON ABOVE LINE AT 1795 FEET SET HUB FOR INITIAL POINT OF SURVEY SAID HUB BEING IN THE CENTER OF STATE ROAD NO. 8 THENCE FOLLOWING STATE ROAD AS FOLLOWS:

COURSES	DISTANCE:
N.39° 07' EAST	445 FEET
N.56° 41' EAST	320 FEET
N.17° 31' EAST	182 FEET
N.53° 31' EAST	180 FEET
N.29° 31' EAST	282 FEET
N.46° 35' EAST	494 FEET
N.88° 50' EAST	223 FEET
S.49° 50' EAST	540 FEET
S.30° 24' EAST	192 FEET
S.02° 42' EAST	220 FEET
S.15° 58' EAST	210 FEET
S.24° 27' EAST	380 FEET
S.02° 37' EAST	425 FEET
S.47° 24' EAST	1000 FEET

TO A POINT MARKED BY $\frac{1}{2}$ INCH IRON PIPE, SAID PIPE BEING 140 FEET; FROM CENTER LINE OF THE S. P. & S. R. R. AND ON THE WEST LINE OF OLD COUNTY ROAD AND PARALLELING THE S. P. & S. R. R. 140 FEET DISTANT; SOUTH 69° 25' WEST 544 FEET TO THE EAST END OF GREENLEAF SLOUGH; THENCE FOLLOWING SAID SLOUGH IN A WESTERLY DIRECTION, MORE