

M.O. #5096
October 4, 1974

FIELD NOTES:

A survey for DON COCHRAN of a tract of land in Section 22,
T. 3 N., R. 13 E., W.M., Skamania County, Washington.

CREW:

David L. Tuttle, Partychief,
Robert Urtich, Chairman.

REFERENCE:

Skamania County Engineer Section Corner reference material

DATE COMPLETED:

August 6, 1974.

On July 25, 1974 our firm was retained by Mr. Don Cochran to survey the south
boundary of the S.W. 1/4 of the S.E. 1/4 of Section 22, T. 3 N., R. 18 E., W.M.

Prior to beginning the survey, we obtained copies of section corner reference
material from the Skamania County Engineer's Office. With the aid of this information
a search was conducted to recover those monuments necessary to survey Mr. Cochran's
tract. The S.W. corner of Section 22 is referenced by a Corps of Engineer's brass
cap monument set along the west bank of Wind River. This monument gives a tie of
56.1 ft. east to the section corner that falls in the river. No trace of the
S. 1/4 corner, its bearing trees, or any reference was found recorded or in the
field. Its position is assumed lost at this point. The S.E. corner of Section 22
was found to be monumented with a 3/4" iron pipe set in a fence corner. There is
a reference poster set on a fence post 66 ft. to the east. This pipe appears to
be the same corner tied by BPA during the course of their route survey for the
Bonneville-Coulee power line. No bearing trees are left due to logging and clearing
of the land around. Its position is assumed to be correct judging from the BPA
ties and Dept. of Natural Resources reference posters.

A traverse was run between the S.E. and S.W. corners of Section 22. The line was
then calculated to its true position and south line of Mr. Cochran's tract set.
The S. 1/4 corner was set midway and monumented with a 1" iron pipe. Two new
bearing trees were blazed in reference to the corner. A 14" fir bears N. 2° E.
28.5 ft. and a 9" fir bears S. 5° W., 5.5 ft. This corner is 17 ft. south of an
existing fence line. The S.E. corner of Mr. Cochran's tract was set midway between
the S. 1/4 and the S.E. corner of Section 22. A 5/8" iron rod was set and two
bearing trees set in reference to it. An 8" maple with a blazed face bears S. 89° W.,
31.5 ft. A 4" fir with a blazed "X" bears S. 16° E., 14.2 ft. There are no fences
in this area or other evidences of ownership.

Corner found and established in the course of the above survey, together with
measured bearings, distances and ties are shown on the attached map, T.E.C. work
order #5096, which by reference is made a part hereof.


CHECKED AND APPROVED:

Signed

David L. Tuttle, Washington Surveyor #11733

Tennessee Engineering Corporation

Donald J. Branton, President



78336

THE STATE OF WASHINGTON
COUNTY OF SKAMANIA
I HEREBY CERTIFY THAT THE WITHIN
INSTRUMENT OF WRITING, FILED BY
David L. Tuttle
Washington Surveyor #11733
AT 11 A.M. OCT 21 1974
WAS RECORDED IN BOOK 1
OF SURVEYS AT PAGE 28
RECORD OF SKAMANIA COUNTY, WASH.
SEP 1974
COUNTY CLERK
E. Mayfield



