

OCT 4 2 19 1991

A DEPENDENT SURVEY of the West line of the
NW 1/4, of Section 3, Township 6 North, Range 5 East
of the Willamette Meridian.

SKAMANIA COUNTY, WASHINGTON

LEGEND

- 1) = A corner FOUND during this survey
- 2) = A new corner SET during this survey
- 3) = A corner calculated only
- 4) = A GLO bearing and/or distance of record
- 5) = An original Bearing Tree, scribed by the GLO
- 6) = A Reference Point, usually a tree with scribing and/or a location tag, referencing a corner
- 7) = the General Land Office (original survey)
- 8) = DNR = Washington State Dept. of Natural Resources
- 9) = "ref-post" = A 6 foot steel fence post with location tag
- 10) = A line marked in the field with painted blazes

NOTES

- 1) Refer to the "LAND CORNER RECORD" forms for additional corner information, filed for each corner shown hereon with the County of Skamania, State of Washington.
- 2) This survey was conducted using a "Wild T-1" theodolite (least read 6"), equipped with a "Wild DI-4" EDM, calibrated on the NGS baseline located at Kelso, WA. Double angles and double distances were taken during a coordinate traverse, beginning at the Section Corner and running Southerly to the 1/4 Corner, resulting in the information shown hereon.

AUDITOR'S CERTIFICATE

Filed for record this 4th day of October, 1991
at 2:19 P. M., in BOOK 3 of SURVEYS, at
PAGE 59, at the request of HAMPSTUR CORPORATION

Darryl M. Olson by P. Slawny
COUNTY AUDITOR DEPUTY AUDITOR

SURVEYOR'S CERTIFICATE


This map correctly represents a survey made by me or under my direction, in conformance with the requirements of the Survey Recording Act of 1973, at the request of PLUM CREEK TIMBER COMPANY, L.P., in August of 1991.

Calvin Hampton
CALVIN J. HAMPTON, PLS
Certificate no. 18,087

Date signed: 8/20/91



HAMPSTUR CORPORATION



P.O. Box 368
Kelso, Washington 98626
Phone: (206) 423-8166

Calculated by: C. J. HAMPTON
Checked by: P. R. GUSTIN
Drawn by: C. J. HAMPTON
Completion date: 8-16-91
Field Book no.: PS-127
Contract no.:
HAMPSTUR JOB no.: 91-634
Sheet no. 1 of 1

BASIS of BEARING:
The GLO record bearing, as shown. Compass dec'l. = 20°E.



SCALE: 1 inch = 200 feet

GLO CALL—22.70 CHS.
(FROM THE NORTH)
"TOP OF BLUFF"
FD. AT 1510 FT.

GLO CALL—25.90 CHS.
(FROM THE NORTH)
"2 LK. CREEK"
FD. AT 1714 FT.

GLO CALL—38.00 CHS.
(FROM THE NORTH)
"TOP OF STEEP ASCENT"
FD. AT 2500 FT.

S.33 S.34
S.4 S.3
T.7 N. R.5 E.
T.6 N. R.5 E.

SECTION CORNER

Fd. DNR concrete mon. with stamped brass cap, as set in 1968 from original evidence. Fd. remains of 2 original BT's.

References

-19" HEMLOCK, N85°W—12.4'
-28" CEDAR, S14°W—35.6'
-7" W. FIR, S56°E—53.4'
-3" W. FIR, N12°E—21.9'
-"REF-POST", EAST—5.0'

T.7 N. R.5 E.
33 | 34
4 | 3
T.6 N. R.5 E.
1968

PLUM CREEK TIMBER COMPANY

1/4 CORNER

Fd. original stone clearly marked "1/4". Replaced stone with a 3/4"x36" galv. iron pipe and stamped brass cap. (Placed stone on East side of pipe). Fd. no BT's.

References

-14" FIR, S62°W—9.4'
-14" FIR, S29°E—7.9'
-"REF-POST", NORTH—3.0'

