

BOOK 133 PAGE 172

LAND CORNER RECORD

(THIS FORM PRESCRIBED BY THE PUBLIC LAND SURVEY OFFICE, DEPARTMENT OF NATURAL RESOURCES, PURSUANT TO RCW 56.09. ALPHA-NUMERIC INDEX DIAGRAM ON THE BACK.)

CORNER INDEXING INFORMATION:

TWP 3N RGE 8E CORNER CODE T-17
(Willamette Meridian) (See instructions on back of LCR)

ADDITIONAL IDENTIFIER: (e.g., BLM designation for the corner, street intersection, plat name, block, lot, etc.)

EAST 1/4 CORNER SECTION 27

COUNTY: **SKAMANIA**

AUDITOR'S USE

LAND SURVEYOR INFORMATION: (or Public Officer as per RCW 58.09.090)

This corner record correctly represents work performed by me or under my direction in conformance with the Survey Recording Act.


COMPANY OR AGENCY: OLSON ENGINEERING INC.
1111 BROADWAY
ADDRESS: VANCOUVER, WA 98660



WASHINGTON PLANE COORDINATES: N: E:

ORDER: _____ ZONE: _____ DATUM (Date of adjustment): _____

CORNER INFORMATION: Use the space below to provide the following information regarding the corner:
(1) Pertinent Corner History, (2) Evidence Found at the Corner, and (3) Corner Perpetuation Information. Please
 title and number the parts of your discussion accordingly. If additional space is needed use the back. (For (3),
 diagram the references. Also, provide the cross-reference to a map of record, if applicable, the surveyor's field
 book no./page no., and the date of work.) (See the back of this form for the requirements of the Survey Recording
 Act.)



In 1875, Smith and Spray, surveyors for the G.L.O. set a maple post at the East quarter of Section 27. The bearing trees are as follows: a maple 12" in diameter bears South 55° East, 22 links distance, a maple 14" in diameter North 30° West 35 links distance. We calculated the said quarter corner, based on a 1935 United States Corps of Engineers plat, which shows it being 2643.04 North from the Northeast corner of Section 34.

Reference Surveys
U.S. Corps of Engineers - R 0-17-6
Wall & Tenneson - Recorded February 1955

OLSON LAND SURVEYORS
ENGINEERS (200) 885-1385
1111 BROADWAY, VANCOUVER, WA 98101

DATE OF FORM: 2/92

MARK THE CORNER LOCATION ON THE DIAGRAM BELOW AND FILL IN THE CORNER CODE BLANK ON THE OTHER SIDE:

(1) For corners located at the intersection of two lines (Section corners, quarter corners and sixteenth corners):

(a) The corner code is the alpha-numeric coordinate from the diagram below that corresponds to the appropriate intersection of lines.

(2) For corners that are not located at the intersection of two lines (Meander corners, DLC's, HES's, reservation boundaries, mining claims, etc.):

(a) For corners that are on one line only the corner code is the line designation and the related line segment; i.e., a corner on line 5 between "B" and "C" is designated BC-5.

(b) For corners that are between lines the corner code is both line segments; i.e., a corner in the SE1/4 of the SE1/4 of section 18 is designated MN-4-5.

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
A																									
B																									
C		6			5			4				3			2					1					
D																									
E																									
F																									
G		7			8			9				10			11					12					
H																									
J																									
K																									
L		18			17			16				15			14					13					
M																									
N																									
O																									
P		19			20			21				22			23					24					
Q																									
R																									
S																									
T		30			29			28				27			26					25					
U																									
V																									
W																									
X		31			32			33				34			35					36					
Y																									
Z																									

RCW 58.09.060 (2) requires the following information on this form: an accurate description and location, in reference to the corner position, of all monuments and accessories (a) found at the corner and (b) placed or replaced at the corner; (c) basis of bearings used to describe or locate such monuments or accessories; and (d) corollary information that may be helpful to relocate or identify the corner position.

SPACE FOR ADDITIONAL COMMENT: