

Aug 12 9 27 AM '93

AUDITOR  
GARY M. OLSON

A DEPENDENT RE-SURVEY OF:  
**SECTION 35, T.3N. R.5E., W.M.**  
FOR—  
**JOE ZUMSTEIN, JR.**  
AS SITUATED WITHIN:  
**SKAMANIA COUNTY, WASHINGTON**

**LEGEND**

- 1) = A corner FOUND or SET during a previous survey, as described
- 2) = A new corner SET during this survey, as described
- 3) = A corner calculated only—not set this survey
- 4) = A Bearing and/or Distance of record
- 5) = An Original Bearing Tree, scribed by the GLO
- 6) = A Reference Point, usually a tree with scribing and/or a location tag
- 7) = The General Land Office
- 8) = A Galvanized Iron Pipe
- 9) = The Department of Natural Resources
- 10) = Information scribed on R.P.s or B.T.s
- 11) = A 6 ft. steel fence post with location tag
- 12) = A 3/4"x36" GIP with a 3" stamped brass cap
- 13) = A line marked during this survey painted blazes, stakes and flagging

**NOTES**

- 1) Refer to the 1982 "RECORD OF SURVEY" of Section 34, T3N R5E, by OLSON ENGINEERING, under the direction of Jerry Olson, LS no. 9,025, as recorded in BOOK 2 of SURVEYS, at PAGE 98, with Skamania County, Washington.
- 2) Refer to the 1992 "RECORD OF SURVEY" of Section 36, T3N R5E, by GEORGE FORD, LS no. 22,330, as recorded in BOOK 3 of SURVEYS, at PAGE 100, with Skamania County, Washington.
- 3) All bearings and distances shown to the "new R.P.s" are to the center of the tree, referenced by an aluminum nail in a small blaze in the side center. Each R.P. also has a blue band of paint around the tree and a reference tag attached.
- 4) This survey was conducted by means of closed traverses between existing corners and/or prior control, using a "Wild T-1" theodolite (least read 6"), equipped with a "Wild DI-4" electronic distance meter, calibrated on the NGS baseline located at Kelso, Washington. The relative accuracy of this control exceeds 1:10,000.

**SURVEYOR'S CERTIFICATE**

This map correctly represents a survey made by me or under my direction, in conformance with the requirements of the Survey Recording Act of 1973, at the request of JOE ZUMSTEIN, JR. in NOVEMBER, 1992 and APRIL, 1993.


GEORGE J. FORD, PLS  
Certificate no. 22,330

Date signed: 7-12-93

**AUDITOR'S CERTIFICATE**

Filed for record this 12<sup>th</sup> day of August, 1993  
at 9:27 A.M., in BOOK 3 of SURVEYS, at  
PAGE 122, at the request of HAMPSTUR CORPORATION.

Gary M. Olson by P. Laury  
COUNTY AUDITOR DEPUTY AUDITOR



SCALE: 1 inch = 500 feet

**SECTION CORNER**

Found and accepted 1" G.I.P. w/brass cap, as set and referenced with 3 R.P.s, by double proportion in 1982 (see note no. 1). Corner tied 4/02/93.

(GLO = N00°02'W—40.00 CHS.)  
(note - 1) N00°06'23"E—2632.99'  
N01°07'15"W—2632.94'

**1/4 CORNER**

Calculated position of 1" G.I.P. w/brass cap, set and referenced with 3 R.P.s in 1982, from orig. evidence (see note no. 1). Corner not tied this survey.

**S.1/16 CORNER**  
Set "brass mon" in rock seam at toe of bluff on 4/19/93.

**NEW R.P.s**  
-12" FIR, N72°W—30.7'  
SCRIBED CS1/16 S34 RPJ  
-9" FIR, S52°W—21.6'  
SCRIBED CS1/16 S34 RPJ  
-REF-POST, SOUTH—1.0'

**T.3N. R.5E.**  
**T.2N. R.5E.**

**SECTION CORNER**

Found and accepted DNR conc. mon., along with remains of 1 orig. B.T., as previously noted (see note no. 1). Added new R.P.s on 4/19/93.

**NEW R.P.s**  
-9" HEMLOCK, N18°W—12.0'  
SCRIBED CS34 T3NR5E RPJ  
-26" FIR, S45°W—6.5'  
SCRIBED CS3 T2NR5E RPJ

(GLO = S89°58'W—39.83 CHS.)  
(note - 1) N88°46'49"E—2580.72'  
S87°33'59"W—2580.73'

**W.1/16 CORNER**

Set "brass mon" on 4/13/93.

**NEW R.P.s**  
-4" FIR, S10°E—7.9'  
SCRIBED C1/16 S35 RPJ  
-4" FIR, S33°W—16.9'  
SCRIBED C1/16 S35 RPJ

**C.W.1/16 CORNER**  
Set "brass mon" on 4/14/93.

**NEW R.P.s**  
-12" FIR, N78°W—7.3'  
SCRIBED CCW1/16 S35 RPJ  
-8" FIR, S12°E—8.15'  
SCRIBED CCW1/16 S35 RPJ  
-REF-POST, SOUTH—1.0'

**SW.1/16 CORNER**  
Set "brass mon" on 4/14/93.

**NEW R.P.s**  
-12" FIR, N20°E—15.7'  
SCRIBED CSW1/16 S35 RPJ  
-9" FIR, N54°W—7.45'  
SCRIBED CSW1/16 S35 RPJ  
-REF-POST, NORTH—1.0'

**SW.1/4 SW.1/4**  
**36.87 ACRES ±**

**NE.1/4 SW.1/4**  
**37.24 ACRES ±**

**SE.1/4 SW.1/4**  
**36.80 ACRES ±**

**1/4 CORNER**

Found and accepted DNR conc. mon., as set from orig. evidence and referenced in 1982 with 3 R.P.s (see note no. 1). Corner tied 11/19/92.

**C.1/4 CORNER**  
Calculated only

**1/4 CORNER**

Calculated position of 5/8" rebar w/alum. cap, as set in 1992 by single proportion and referenced with 3 R.P.s (see note no. 2). Corner not tied this survey.

**1/4 CORNER**

Set "brass mon" by single proportion on 4/16/93.

**NEW R.P.s**  
-12" FIR, N60°E—6.5'  
SCRIBED C1/4 S35 RPJ  
-12" FIR, S14°E—3.9'  
SCRIBED C1/4 S2 RPJ  
-REF-POST, NORTH—1.0'

**SECTION CORNER**

Found and accepted 5/8" rebar w/alum. cap, as set in 1992 from 3-stump pattern and referenced with 3 R.P.s (see note no. 2). Corner tied 11/16/92.

**BASIS OF BEARING**  
The East line of Section 35, as previously determined by Solar Observation—see note 2.

**SECTION CORNER**

Found and accepted 3/4" G.I.P. with 1 orig. B.T. and 2 old R.P.s as previously recorded (see note no. 2). Added 3" stamped brass cap and new R.P.s on 4/05/93.

**NEW R.P.s**  
-14" FIR, S52°E—36.3'  
SCRIBED CS1 T2NR5E RPJ  
-18" FIR, N55°W—22.9'  
SCRIBED CS35 T3NR5E RPJ  
-14" FIR, S16°W—33.4'  
SCRIBED CS2 T2NR5E RPJ