

FILED FOR RECORD
SKAMANIA CO. WASH
BY Longview Fibre
Nov 21 11 28 AM '00
GARY H. OLSON

RECORD OF SURVEY
FOR
LONGVIEW FIBRE COMPANY
IN
SECTION 4, T 2 N, R 6 E, W.M.
SKAMANIA COUNTY, WASHINGTON

OCTOBER 11, 2000

THE PURPOSE OF THIS SURVEY WAS TO LOCATE THE WEST LINE OF THE NW 1/4 AND THE NORTH LINE OF SECTION 4. THE SURVEY WAS DONE WITH LEICA 399 GPS RECEIVERS AND A LEICA TC805 TOTAL STATION. TERTIARY GPS CONTROL POINTS WERE ESTABLISHED NEAR THE SW SECTION CORNER, THE NW SECTION CORNER AND THE EAST 1/4 CORNER. THE NE SECTION CORNER WAS OCCUPIED WITH A GPS RECEIVER. THE SW SECTION CORNER WAS TIED BY TRAVERSE FROM THE GPS CONTROL. A TRAVERSE WAS RUN FROM GPS CONTROL ALONG THE WEST AND NORTH LINES OF SECTION 4 AND CLOSED ON THE NE SECTION CORNER. THE NORTH AND WEST 1/4 CORNERS WERE DETERMINED LOST AND WERE ESTABLISHED BY SINGLE PROPORTION.

SECTION CORNER

FOUND 4" CONCRETE
MONUMENT WITH 3-1/2"
DNR BRASS CAP, DATED 1962
SEE DNR SECTION CORNER
RECORD DATED 1963 FOR
SECTION 4, T2N, R6E, W.M.
FOR REFERENCES

SECTION CORNER

FOUND 3/4" PIPE
SEE LAND CORNER RECORD
BOOK 2/6 PAGE 3, AFN 82573

1/4 CORNER

SET 2" PIPE WITH
3" STAMPED BRASS CAP
AT PROPORTION POSITION
NEW REFERENCES:
11" D. FIR N73°W - 4.8'
SCRIBED (1/4 S33 BT)
9" D. FIR S38°W - 5.6'
SCRIBED (1/4 S4 BT)

LONGVIEW FIBRE COMPANY
AFN 106251, BOOK 112 PAGE 40

1/4 CORNER

SET 2" PIPE WITH
3" STAMPED BRASS CAP
AT PROPORTION POSITION
NEW REFERENCES:
12" T. FIR EAST - 2.1'
SCRIBED (1/4 S4 BT)
8" D. FIR S46°W - 19.7'
SCRIBED (1/4 S5 BT)
STEEL FENCE POST
NORTH - 2.0'
NOTE: G.L.O. CALLS FOR
28" SILVER PINE S68°E AT 31' LKS (20.5')
18" HEMLOCK N68°E AT 32' LKS (34.3')
CREEK 10' LKS WIDE 1.9 CHNS (125.4') NORTH
OF THE CORNER
WE FOUND A 43' FIR SNAG WITH DNR TAG
DATED 1962. THIS SNAG HAS A WELL DEFINED
BURNED OUT FACE ON THE NE QUADRANT.
THIS WOULD PUT THE BT SW OF THE CORNER
CONTRADICTING THE G.L.O. CALL.
WE ALSO TIED A 24" HEMLOCK SHELL
S72°E AT 8.2', AND A 20" HEMLOCK
STUMP BADLY DECAYED S35°E AT 20.3'.
I COULD NOT DEVELOP A LOGICAL
COMBINATION OF THE FOUND STUMPS TO
SET THE CORNER BASED ON THE LOCAL
EVIDENCE. I CONSIDER THIS CORNER "LOST".
THE CREEK IS 121' NORTH OF THE
PROPORTION POSITION.

SECTION CORNER

FOUND 1/2" REBAR
SEE SURVEY AFN 106486
BOOK 3 PAGE 2



BASIS OF BEARING

BEARINGS ARE STATE PLANE
WASHINGTON SOUTH ZONE NAD83 (91)



SCALE: 1 INCH = 500 FEET
GRID DISTANCES ARE SHOWN


AUDITOR'S CERTIFICATE

FILED FOR RECORD THIS 21st DAY OF November, 2000
AT 11:28 AM IN BOOK 3 OF SURVEYS AT PAGE 372
AT THE REQUEST OF LONGVIEW FIBRE COMPANY.

139729
AUDITOR'S FILE NUMBER

Angela Moser Dwyer
SKAMANIA COUNTY AUDITOR

LEGEND



SECTION CORNER, 1/4 CORNER
FOUND AS NOTED



SET 2" X 30" PIPE WITH
3" BRASS CAP, STAMPED AS NOTED




CALCULATED POSITION



RECORD BEARING AND/OR DISTANCE
AS NOTED



GOVERNMENT LAND OFFICE RECORD
BEARING AND DISTANCE



LINE MARKED WITH 1/2" X 60" FIBER GLASS RODS
WITH RED AND WHITE FLAGGING BETWEEN RODS
TREES ALONG LINE PAINTED WITH BLUE PAINT

STATE PLANE NAD83 (91) SOUTH ZONE

POINT	NORTHING	EASTING	CONVERGENCE	SCALE FACTOR
SW SEC COR	130465.73	1235343.56	-01°09'04"	1.0000383
W 1/4 COR	133005.07	1235360.58	-01°09'05"	1.0000364
NW SEC COR	135590.14	1235377.91	-01°09'05"	1.0000345
N 1/4 COR	135559.60	1237932.21	-01°08'39"	1.0000345
NE SEC COR	135529.07	1240486.50	-01°08'13"	1.0000345

NOTE: NEW REFERENCES
REFERENCES HAVE AN 8" SPIKE AT BASE OF SCRIBE WITH LONGVIEW
FIBRE COMPANY LOCATION TAG ABOVE SCRIBE. ALL ORIENTED TOWARD
MONUMENT. DISTANCES MEASURED TO SPIKE. BEARINGS TO REFERENCES
TAKEN WITH HAND COMPASS HAVING A DECLINATION OF 21° EAST.

SURVEYOR'S CERTIFICATE

THIS MAP CORRECTLY REPRESENTS A SURVEY MADE BY ME OR
UNDER MY DIRECTION IN CONFORMANCE WITH THE REQUIREMENTS
OF THE SURVEY RECORDING ACT AT THE REQUEST OF LONGVIEW
FIBRE COMPANY IN JUNE 2000.

GEORGE J. FORD, PLS
CERTIFICATE NO. 22330



LONGVIEW FIBRE COMPANY
LONGVIEW, WA 98632