

RECORD OF SURVEY
FOR
LONGVIEW FIBRE COMPANY
IN THE NW 1/4 OF THE SE 1/4 OF
SECTION 23, T 2 N, R 5 E, W.M.
SKAMANIA COUNTY, WASHINGTON

1/4 CORNER

FOUND 3/4" PIPE WITH
ALUMINUM CAP SEE DEPARTMENT
OF FISHERIES SURVEY
WASHOUGAL HATCHERY, DATED 9/80
SEC. 23, T2N, R5E, W.M.

SECTION CORNER

CALCULATED POSITION
BASED ON D.N.R.
SURVEY "UKELELE"
AUDITOR'S FILE NO. 112735
BOOK 3 OF SURVEYS PAGE 68-72

C 1/4 CORNER

FOUND 1" PIPE WITH
2" BRASS CAP
SEE ROS AFN 111079

1/4 CORNER

CALCULATED POSITION

STATE
BOOK 70 PAGE 381

LONGVIEW FIBRE
COMPANY
BOOK 111 PAGE 620

STATE
BOOK 79 PAGE 507

CS 1/16 CORNER

SET 3/4" X 36" PIPE
WITH 2" BRASS CAP
NEW REFERENCES:
10" FIR N20°W AT 13.2'
SCRIBED [CS 1/16 S23 BT]
18" ALDER S16°E AT 13.4'
BARK SCRIBED [CS 1/16 S23 BT]
STEEL FENCE POST
SOUTH AT 1.0'

SECTION CORNER

FOUND DNR ALUMINUM MONUMENT
SEE ROS BOOK 2 PAGE 232
DEPARTMENT OF FISHERIES
MONUMENT N 37°24' E AT 16.82'

1/4 CORNER


CALCULATED POSITION
FOUND DEPARTMENT
OF FISHERIES MONUMENT
N 33°09' E AT 8.47'
FROM CALC. POS.
SEE SURVEY DATED 9/80

N 89°23'50" W -- 2581.58'
(S 89°16'05" W -- 2581.66' ROS AFN 111079)

STATE PLANE NAD83 (91) SOUTH ZONE

POINT	NORTHING	EASTING	CONVERGENCE	SCALE FACTOR
SE SEC COR	114931.19	1219235.36	-1°11'46"	1.0000504
C 1/4 COR	117593.16	1216753.53	-1°12'12"	1.0000484
CS 1/16 COR	116275.75	1216703.75	-1°12'12"	1.0000494

NOTE: NEW REFERENCES
REFERENCES HAVE AN 8" SPIKE AT BASE OF SCRIBE WITH LONGVIEW
FIBRE COMPANY LOCATION TAG ABOVE SCRIBE. ALL ORIENTED TOWARD
MONUMENT. DISTANCES MEASURED TO SPIKE. BEARINGS TO REFERENCES
TAKEN WITH HAND COMPASS HAVING A DECLINATION OF 21° EAST.



LEGEND

SECTION CORNER, 1/4 CORNER FOUND AS NOTED
MONUMENT FOUND AS NOTED
CALCULATED POSITION
SET 3/4" X 36" PIPE WITH 2" BRASS
CAP STAMPED AS SHOWN
RECORD BEARING AND/OR DISTANCE AS NOTED
LINE MARKED WITH 1/2" X 60" FIBER GLASS RODS.
WITH RED AND WHITE FLAGGING BETWEEN RODS.
TREES ALONG LINE PAINTED WITH BLUE PAINT.

THE PURPOSE OF THIS SURVEY WAS TO ESTABLISH THE WEST
LINE OF THE NORTH HALF OF THE SOUTHEAST QUARTER OF
SECTION 23.
THIS SURVEY IS BASED ON PREVIOUS SURVEY BY TERRA
SURVEYING DATED FEBRUARY 1991, RECORDED UNDER
AUDITOR'S FILE NO. 111079. BY PREVIOUS SURVEY DATED
SEPT. 1999, I ESTABLISHED STATE PLANE COORDINATES
FOR THE NORTH QUARTER CORNER AND NORTHWEST SECTION
CORNER. I ORIENTED TERRA'S SURVEY TO STATE PLANE BASED
ON TIE TO SOUTHEAST SECTION CORNER AND THE NORTH QUARTER
CORNER. THE CONTROL FOR THIS SURVEY WAS ESTABLISHED
WITH LEICA 399 GPS RECEIVERS. CONTROL POINTS WERE
ESTABLISHED NEAR THE CENTER SOUTH 1/16 CORNER AND
THE SOUTH 1/4 CORNER. A TRAVERSE WAS CLOSED ON THE
CENTER 1/4 CORNER. A TRAVERSE WAS RUN TO THE SOUTH
EAST SECTION CORNER. TRAVERSES WERE RUN WITH A LEICA
TC-1105. THE CENTER SOUTH 1/16 CORNER WAS ESTABLISHED
BY RADIAL STAKEOUT.



BASIS OF BEARING
BEARINGS ARE STATE PLANE
WASHINGTON SOUTH ZONE NAD83 (91)

0' 500' 1000' 1500'
SCALE: 1 INCH = 500 FEET
GRID DISTANCES ARE SHOWN

AUDITOR'S CERTIFICATE

FILED FOR RECORD THIS 17th DAY OF May, 2001
AT 4:53 PM IN BOOK 3 OF SURVEYS AT PAGE 392
AT THE REQUEST OF LONGVIEW FIBRE COMPANY.

141122
AUDITOR'S FILE NUMBER

George J. Ford
SKAMANIA COUNTY AUDITOR

SURVEYOR'S CERTIFICATE

THIS SURVEY CORRECTLY REPRESENTS A SURVEY MADE BY ME OR
UNDER MY DIRECTION IN CONFORMANCE WITH THE REQUIREMENTS
OF THE SURVEY RECORDING ACT AT THE REQUEST OF LONGVIEW
FIBRE COMPANY IN FEBRUARY 2001.

GEORGE J. FORD, PLS
CERTIFICATE NO. 22330

LONGVIEW FIBRE COMPANY
LONGVIEW, WA 98632

