

150015

BOOK 249 PAGE 83

Norm Ward

O'Dowry

LAND CORNER RECORD

GRANTOR/SURVEYOR/PUBLIC OFFICER: This corner record correctly represents work performed by me or under my direction, in conformance with the Survey Recording Act.

COMPANY OR AGENCY: USDA Forest Service
 ADDRESS: Gifford Pinchot National Forest
 10600 NE 51st Circle
 Vancouver WA 98682



Don Karsch
 Forest Land Surveyor

8/7/2003
 Date

GRANTEE: PUBLIC

LEGAL: TWP: 4 NORTH RGE: 7 EAST CORNER CODE: GH-16
 ADDITIONAL IDENTIFIER: (BLM designation, street, or plat names, block, lot, etc.)

CNNSE 1/256 S10

COUNTY: SKAMANIA

WASHINGTON PLANE COORDINATES: N:

E:

ORDER: ZONE: DATUM: (DATE OF ADJUSTMENT:

CORNER INFORMATION: Discuss the history, evidence found, and perpetuation of the corner. Diagram the references; provide the date of work; and if applicable, a reference to a map of record and/or the field book/page no. Use the back, if needed.

Corner History:

This corner was originally established by Larry D. Bishop, PLS#16337, in May of 1982. He set a 2 1/2" x 30" aluminum pipe with 2 1/2" aluminum cap. He also marked 2 bearing trees:

- A 11" D.Fir - N59°W, 17.2 ft. (7.2 ft. record) scribed "CNNSE 1/256 S10."
- A 13" D.Fir - N34°E, 10.4 ft. scribed "CNNSE 1/256 S10."

On July 30, 2003 I found the corner monument, set 4" above ground, in good condition.

Found Bishop BT's:

- An 11" now 13" D.Fir live with overgrown face bears N59°W, 17.2 ft.
- A 13" D.Fir stump at record bearing and distance with visible overgrown face.

New BT's Established:

- A 16" D.Fir bearing N44°E, 29.4 ft. scribed "CNNSE 1/256 S10 BT"

Placed "BT" tags and "Land Survey Monument" signs on all BT's. Painted a 6" red band and faces of all standing BT's.

Forest Service property lines leading south and east are brushed, blazed, and posted w/USFS carsonite posts. Bearings are by compass w/ 18° East declination. Distances are to nail in side center of bearing tree.

Witnessed by: Mariah Midland, Alysha Miller, Stevenson High School

This form is in compliance with the intent of RCW 65.04.045 and prescribed by the Public Land Land Survey Office, Department of Natural Resources - 1/97.

MARK THE CORNER LOCATION BELOW AND FILL IN THE CORNER CODE BLANK ON THE OTHER SIDE.
For corners at the intersection of two lines, the corner code is the alphanumeric coordinate that corresponds to the appropriate intersection of lines.

For corners that are only on one line, the corner code is the line designation and the related line segment; i.e., a corner on line 5 between 'B' and 'C' is designated BC-5.

For corners that are between lines, the corner code is both line segments; i.e., a corner in the SE1/4 of the SE1/4 of section 18 is designated MN 4-5.

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
A																									
B																									
C																									
D																									
E																									
F																									
G																									
H																									
I																									
J																									
K																									
L																									
M																									
N																									
O																									
P																									
Q																									
R																									
S																									
T																									
U																									
V																									
W																									
X																									
Y																									
Z																									

RCW 58.09.060 (2) requires the following information on this form: an accurate description and location, in reference to the corner position, of all monuments and accessories (a) found at the corner and (b) placed or replaced at the corner; (c) basis of bearings used to describe or locate such monuments or accessories; and (d) corollary information that may be helpful to relocate or identify the corner position.

SPACE FOR ADDITIONAL COMMENT:

SP

Bishop
BT
D-FIR
1/2 N 59° W
17.2'

OLD BT
STUMP
1/2 N 59° W
17.2'

NEW BT
16" D-FIR
N 44° E
29.4'

Found 2 1/2" x 30" aluminum pipe
w/ 2 1/2" aluminum cap found about
4" above ground.

1/256
128
256

RTW
CNNS
1/256
128
256

NORTH