

SET 1/2" X 30" IRON ROD WITH YELLOW PLASTIC CAP MARKED "WYEAST PLS 29288"

FOUND MONUMENT AS NOTED

CALCULATED POSITION


REFERENCES:

1) BOOK I OF SURVEYS, PAGE 230
2) BOOK T OF CITY PLATS, PAGE 19
3) BOOK T OF CITY PLATS, PAGE 105
4) CLARK ELDRIDGE JULY 1966 SURVEY FOR PLATS, PAGE 55
6) C.R.P. 91-7 RYAN-ALLEN ROAD
7) C.R.P. 58-11 FOSTER CREEK ROAD

FOR G.P.

8	L7	16 1	L5	L <b>4</b>	L3	L2	L1	LINE	
6.09	13.81	20.10	56.37	40.00	23.00	0.53	15.00	LENGTH	LINE TABLE
N00'54'29"E	N01.47'45"W	S83'21'06"E	S00'50'59"W	S00°50'59"W	S79°24'36"W	N00'54'29"E	N89*05'31"W	BEARING	)LE

C2	C1	CURVE	
31'09'19"	38'38'04"	DELTA ANGLE   RADIUS   ARC	
205.00	210.00	RADIUS	CUI
111.47	141.60		CURVE TABLE
57.15	73.61	TANGENT	ш
110.10	138.94	CHORD	
N56°21'15"E	S60*05'38"W	TANGENT CHORD CHORD BEARING	



SURVEYOR'S CERTIFICATE

THIS MAP CORRECTLY REPRESENTS A SURVEY MADE BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE REQUIREMENTS OF THE SURVEY RECORDING ACT AT THE REQUEST OF EVELYN SKAAR

KEVIN DOWD PLS 2 Ċ

AUDITOR'S CERTIFICATE

FILED FOR RECORD THIS 5th DAY OF JUNE AT 12:52 A. IN AUDITOR'S FILE NO. 20071166311

COUNTY AUDITOR BY COCK depuny

THIS SURVEY WAS CONDUCTED DURING JANUARY THROUGH MAY, 2007, BY CLOSED TRAVERSE USING A 5" TOTAL STATION AND ACCESSORIES. THIS SURVEY MEETS THE MINIMUM STANDARDS FOR SURVEYS AS PER WAC 332-130-090.

RECORD 유 SURVEY

LOCATED IN THE BAUGHMAN D.LC.
AND THE IMAN D.L.C
IN THE NORTHEAST QUARTER
OF SECTION 2
T2 NORTH, R7 EAST, W.M.
IN THE CITY OF STEVENSON
SKAMANIA COUNTY, WASHINGTON

FOR: EVELYN SKAAR

KEVIN DOWD 4399 WOODWORTH DRIVE MT HOOD, OR 97041 (541) 352-6065 WYEAST SURVEYS