

LAND CORNER RECORD

GRANTOR/ SURVEYOR/ PUBLIC OFFICER: This corner record correctly represents work performed by me or under my direction in conformance with the Surveying Recording Act.

COMPANY OR AGENCY: LONGVIEW TIMBER

ADDRESS: PO BOX 667
LONGVIEW, WA 98632



GRANTEE: PUBLIC

SEAL/SIGNATURE/DATE

LEGAL: SECTION 33 **TWP:** 3 NORTH **RGE:** 5 EAST **CORNER CODE:** W-11
ADDITIONAL IDENTIFIER: (e.g., BLM designation, street intersection, plat, block, lot, etc.)

COUNTY: SKAMANIA

WASHINGTON PLANE COORDINATES: **N:** **E:**
ORDER: **ZONE:** **DATUM (Date of adjustment):**

CORNER INFORMATION: Provide: (1) Pertinent History, (2) Evidence Found, and (3) Corner Perpetuation Information (diagram the references; provide the date of work; and, if applicable, reference to a map of record and/or the field book/page no.) Additional space is available on the back.

This corner was originally established by Olson Engineering during a retracement survey in 1981 found in Book 2 Page 97 DNR website .

Olson notes setting a 1" iron pipe with a brass cap with the following Bearing Trees:

8" Fir bears N 20° W at 9.73' with railroad spike and three blazes facing corner.

18" Fir bears N 85° E at 20.94' with railroad spike and three blazes facing corner.

14" Fir bears S 15° E at 9.95' with railroad spike and three blazes facing corner.

In 2011 Longview Timber survey crew found corner Olson set and bearing trees listed in survey along with a 6' steel fence post north 1.0' from corner.

8" Fir now a dead 9" bears N 20° W at 9.73' with railroad spike and three blazes facing corner.

18" Fir now a 31" bears N 85° E at 20.94' with railroad spike and three blazes facing corner.

14" Fir now a 25" bears S 15° E at 9.95' with railroad spike and three blazes facing corner.

MARK THE CORNER LOCATION BELOW AND FILL IN THE CORNER CODE BLANK ON THE OTHER SIDE:
For corners at the intersection of two lines, the corner code is the alphanumeric coordinate that corresponds to the appropriate intersection of lines.

For corners that are only on one line, the corner code is the line designation and the related line segment: i.e., a corner on line 5 between "B" and "C" is designated BC-5.

For corners that are between lines, the corner code is both line segments; i.e., a corner in the SE 1/4 of the SE 1/4 of section 18 is designated MN 4-5.

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
A																									
B																									
C		6					5				4				3				2				1		
D																									
E																									
F																									
G		7					8				9				10				11				12		
H																									
J																									
K																									
L		18					17				16				15				14				13		
M																									
N																									
O																									
P		19					20				21				22				23				24		
Q																									
R																									
S																									
T																									
U		30					29				28				27				26				25		
V																									
W																									
X		31					32				33				34				35				36		
Y																									
Z																									

RCW 58.09.060 (2) requires the following information on this form: an accurate description and location, in reference to the corner position, of all monuments and accessories (a) found at the corner and (b) placed or replaced at the corner; (c) basis of bearings used to describe or locate such monuments or accessories; and (d) corollary information that may be helpful to relocate or identify the corner position.

SPACE FOR ADDITIONAL COMMENT:

NOTES:

