

LAND CORNER RECORD

GRANTOR/ SURVEYOR/ PUBLIC OFFICER: This corner record correctly represents work performed by me or under my direction in conformance with the Surveying Recording Act.

COMPANY OR AGENCY: LONGVIEW TIMBER

ADDRESS: PO BOX 667
LONGVIEW, WA 98632



GRANTEE: PUBLIC SEAL/SIGNATURE/DATE
LEGAL: SECTION 33 TWP: 3 NORTH RGE: 5 EAST CORNER CODE: Z-11
ADDITIONAL IDENTIFIER: (e.g., BLM designation, street intersection, plat, block, lot, etc.)

COUNTY: SKAMANIA

WASHINGTON PLANE COORDINATES: N: E:
ORDER: ZONE: DATUM (Date of adjustment):

CORNER INFORMATION: Provide: (1) Pertinent History, (2) Evidence Found, and (3) Corner Perpetuation Information (diagram the references; provide the date of work; and, if applicable, reference to a map of record and/or the field book/page no.) Additional space is available on the back.

This corner was originally established by Deputy Surveyor Charles Sears in June, of 1883 under Contract No. 284.
Sears notes setting a post with the following Bearing Trees:
40" Fir bears North 28 links
48" Fir bears S 19° E 41 link

In Record of Survey in Book 2 at page 97 Olson Engineering performed a retracement survey and found no original evidence and set a 1" x 36" iron pipe topped with a 3" Brass Cap at a single proportional distance between the Southeast and Southwest Section Corners with the following references.

42" stump with R/R spike at center N 63° W 56.10'
26" stump with R/R spike at center S 14° E 52.73'
50" stump with R/R spike at center N 13° E 137.03
All existing references were recovered.

I also set the following new references.

14" Fir N 89° W 23.08' scribed [T3N R5E 1/4 S33 BT]
14" Fir S 29° W 31.00' scribed [T2N R5E 1/4 S4 BT]

MARK THE CORNER LOCATION BELOW AND FILL IN THE CORNER CODE BLANK ON THE OTHER SIDE:

For corners at the intersection of two lines, the corner code is the alphanumeric coordinate that corresponds to the appropriate intersection of lines.

For corners that are only on one line, the corner code is the line designation and the related line segment: i.e., a corner on line 5 between "B" and "C" is designated BC-5.

For corners that are between lines, the corner code is both line segments; i.e., a corner in the SE 1/4 of the SE 1/4 of section 18 is designated MN 4-5.

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
A																									
B																									
C		6					5				4				3				2				1		
D																									
E																									
F																									
G		7					8				9				10				11				12		
H																									
J																									
K																									
L		18					17				16				15				14				13		
M																									
N																									
O																									
P		19					20				21				22				23				24		
Q																									
R																									
S																									
T		30					29				28				27				26				25		
U																									
V																									
W																									
X		31					32				33				34				35				36		
Y																									
Z																									

RCW 58.09.060 (2) requires the following information on this form: an accurate description and location, in reference to the corner position, of all monuments and accessories (a) found at the corner and (b) placed or replaced at the corner; (c) basis of bearings used to describe or locate such monuments or accessories; and (d) corollary information that may be helpful to relocate or identify the corner position.

SPACE FOR ADDITIONAL COMMENT:

NOTES:

New References have a Bearing Tree Tag above the scribe and an 8" spike at side center of tree, all oriented toward monument.
Bearings to references taken with hand compass having a declination of 21° East.
Distances measured to spike.



NOT TO SCALE

