

LAND CORNER RECORD

GRANTOR/ SURVEYOR/ PUBLIC OFFICER: This corner record correctly represents work performed by me or under my direction in conformance with the Surveying Recording Act.

COMPANY OR AGENCY: LONGVIEW TIMBER

ADDRESS: PO BOX 667
LONGVIEW, WA 98632



GRANTEE: PUBLIC

SEAL/SIGNATURE/DATE

LEGAL: SECTION 32 TWP: 3 NORTH RGE: 5 EAST CORNER CODE: V-5
ADDITIONAL IDENTIFIER: (e.g., BLM designation, street intersection, plat, block, lot, etc.)

COUNTY: SKAMANIA

WASHINGTON PLANE COORDINATES: N: E:
ORDER: ZONE: DATUM (Date of adjustment):

CORNER INFORMATION: Provide: (1) Pertinent History, (2) Evidence Found, and (3) Corner Perpetuation Information (diagram the references; provide the date of work; and, if applicable, reference to a map of record and/or the field book/page no.) Additional space is available on the back.

This corner was originally established by Deputy surveyor Robert A Webster in 1882, under contract #385. Webster notes setting a post with the following bearing trees.

- 12" Hemlock bears N40°E at 38 Links
- 36" Hemlock bears S67°E at 67 Links
- 20" Hemlock bears S26°W at 38 Links
- 36" Cedar bears N13°W at 24 Links

In 1981 Olson Engineering found and held a 1" iron pipe for corner location, they also note finding a 48" Cedar stump N10W 15.77' with burned out face and a 24" Hemlock stump with no marks N43°E at 26.5', see record of survey Book 2 Page 96. Olson added the following references:

- 48" Snag bears N10°W at 15.77' with burnt face added location tag
- 12" Alder bears S14°E at 1.50' with scribe and location tag.
- 16" Hemlock bears S51°W at 14.30' with nail, washer, scribe and location tag.

In 2012 Longview Timber survey crew found and accepted the 1" iron pipe for corner and references Olson added during 1981 survey.

Existing references:

- 48" burnt snag N10°W at 15.77'
- 12" Alder S14°E at 1.50' now a rotten stump
- 16" Hemlock S51°W at 14.13' now a 26" Hemlock with healed face

Added new reference:

- 32" Fir N36°W at 23.9' scribed [T3NR5ES30BT]
- 6' T post 1.0' North

MARK THE CORNER LOCATION BELOW AND FILL IN THE CORNER CODE BLANK ON THE OTHER SIDE:

For corners at the intersection of two lines, the corner code is the alphanumeric coordinate that corresponds to the appropriate intersection of lines.

For corners that are only on one line, the corner code is the line designation and the related line segment: i.e., a corner on line 5 between "B" and "C" is designated BC-5.

For corners that are between lines, the corner code is both line segments; i.e., a corner in the SE 1/4 of the SE 1/4 of section 18 is designated MN 4-5.

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
A																									
B																									
C		6					5				4				3				2				1		
D																									
E																									
F																									
G		7					8				9				10				11				12		
H																									
J																									
K																									
L		18					17				16				15				14				13		
M																									
N																									
O																									
P		19					20				21				22				23				24		
Q																									
R																									
S																									
T		30					29				28				27				26				25		
U																									
V																									
W																									
X		31					32				33				34				35				36		
Y																									
Z																									

RCW 58.09.060 (2) requires the following information on this form: an accurate description and location, in reference to the corner position, of all monuments and accessories (a) found at the corner and (b) placed or replaced at the corner; (c) basis of bearings used to describe or locate such monuments or accessories; and (d) corollary information that may be helpful to relocate or identify the corner position.

SPACE FOR ADDITIONAL COMMENT:

NOTES:

