



THIS SURVEY WAS CONDUCTED DURING MARCH THROUGH MAY, 2014 BY CLOSED TRAVERSE USING A 3 SECOND TOTAL STATION AND ACCESSORIES. THE TRAVERSE MEETS THE MINIMUM STANDARDS FOR SURVEYS AS PER WAC 332-130-190. THE TRAVERSE WAS ADJUSTED BY LEAST SQUARES ADJUSTMENT.

THIS BOUNDARY LINE ADJUSTMENT IS EXEMPT FROM CITY AND STATE PLATTING REGULATIONS AS PROVIDED BY RCW 58.17.040(6).

Kevin Dowd
6-9-2014
CITY PLANNING DIRECTOR

SURVEYOR'S CERTIFICATE

THIS MAP CORRECTLY REPRESENTS A SURVEY MADE BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE REQUIREMENTS OF THE SURVEY RECORDING ACT AT THE REQUEST OF THE CHERYL BROWN TRUST.

Kevin Dowd
KEVIN DOWD PLS 29288

AUDITOR'S CERTIFICATE

FILED FOR RECORD THIS 9th DAY OF June 2014 AT 2:05 IN AUDITOR'S FILE NO. 2014 000911 AT THE REQUEST OF WYEAST SURVEYS.

Melissa Anderson
COUNTY AUDITOR Deputy

CHERYL BROWN TRUST BOUNDARY LINE ADJUSTMENT

LOCATED IN LOT 8 OF STEVENSON PARK ADDITION IN THE HENRY SHEPARD D.L.C. IN SECTION 36, T3 NORTH, R7 EAST, W.M. IN THE CITY OF STEVENSON SKAMANIA COUNTY, WASHINGTON

WYEAST SURVEYS
KEVIN DOWD
4399 WOODWORTH DR.
MT HOOD, OR 97041
(541) 352-6065

LINE TABLE		
LINE	BEARING	LENGTH
L1	S00°01'12"E	25.31
L2	S00°01'12"E	33.27
L3	(N85°30'E)	(55)

CURVE TABLE						
CURVE	DELTA ANGLE	RADIUS	ARC	TANGENT	CHORD BEARING	CHORD
C1	7°56'17"	286.48	39.69	19.88	N12°16'13"E	39.66
C2	31°33'43"	286.48	157.81	80.96	N07°28'47"W	155.82
C3	50°45'00"	358.10	317.19	169.85	N48°38'09"W	306.92
C4	11°58'00"	572.96	119.67	60.05	S68°01'39"E	119.45
C5	27°34'08"	261.48	125.82	64.15	N09°28'35"W	124.61
C6	7°44'50"	333.10	45.04	22.55	N27°08'04"W	45.01
C7	43°00'10"	333.10	250.00	131.22	N52°30'34"W	244.18
C8	6°25'20"	597.96	67.02	33.55	S70°47'59"E	66.99
C9	0°43'39"	597.96	7.59	3.80	S67°13'29"E	7.59