

LAND CORNER RECORD

GRANTOR/SURVEYOR/PUBLIC OFFICER: This corner record correctly represents work performed by me or under my direction in conformance with the Survey Recording Act.

COMPANY OR AGENCY: STATE OF WASHINGTON
DEPARTMENT OF NATURAL RESOURCES
ADDRESS: 601 BOND ROAD
CASTLE ROCK, WA. 98611
(360) 740-6818

JOHN SHACKELFORD, PLS 22349
DIVISION LAND SURVEY



GRANTEE: PUBLIC SEAL/SIGNATURE/DATE

LEGAL: TWP: 14 NORTH RGE: 3 WEST CORNER CODE: (J21)
ADDITIONAL IDENTIFIER: (BLM designation, street or plat names, block, lot, etc.)
SECTION CORNER COMMON TO SECTIONS 11, 12, 13, AND 14,
TOWNSHIP 3 NORTH, RANGE 6 EAST, WILLAMETTE MERIDIAN.

COUNTY: SKAMANIA

WASHINGTON PLANE COORDINATES: N: E:

ORDER: ZONE: WAS DATUM (Date of adjustment):

CORNER INFORMATION: Discuss the history, evidence found, and perpetuation of the corner. Diagram the references; provide the date of work; and, if applicable, a reference to a map of record and/or the field book/page no. Use the back, if needed.

HISTORY:

1903 - G.L.O. SURVEYOR, ROBERT F. WHITMAN, UNDER CONTRACT #600, SET A POST.
1988 - JERRY C. OLSON, PLS #9025, SET A 1" IRON PIPE WITH BRASS CAP, AS
PER RECORD OF SURVEY FILED IN BOOK 3 OF SURVEYS AT PAGES 14 AND 15,
SKAMANIA COUNTY RECORDS.

EVIDENCE:

06/23/2014: FOUND A 2 1/2" BRASS CAP ALONG WITH THE FOLLOWING REFERENCES:
-A 36" FIR SNAG BEARS S33°E, 33.2'.
(ORIGINAL G.L.O. BT).
-A ROTTED, 20" HEMLOCK STUB BEARS S80°W, 25.2'.
(ORIGINAL G.L.O. BT).
-PARTIAL REMAINS OF HEMLOCK ROOTS BEAR N11°W, 34.3'.
(ORIGINAL G.L.O. BT).
-A 24" FIR BEARS N54°W, 38.93'.
(OLSON REFERENCE TREE).
-21" FIR BEARS S69°E, 34.61'.
(OLSON REFERENCE TREE).
-A 14" FIR BEARS S14E°, 34.71'.
(OLSON REFERENCE TREE).

PERPETUATION:

06/23/2014: THE FOLLOWING NEW REFERENCES WERE NOTED:
-A 13" FIR BEARS N44°W, 8.31'.
NAIL SET LEFT SIDE CENTER.
-A 10" HEMLOCK BEARS S68W, 12.37'.
NAIL SET LEFT SIDE CENTER.

MARK THE CORNER LOCATION BELOW AND FILL IN THE CORNER CODE BLANK ON THE OTHER SIDE:
For corners at the intersection of two lines, the corner code is the alphanumeric coordinate that corresponds to the appropriate intersection of lines.

For corners that are only on one line, the corner code is the line designation and the related line segment; i.e., a corner on line 5 between "B" and "C" is designated BC-5.

For corners that are between lines, the corner code is both line segments; i.e., a corner in the SE1/4 of the SE1/4 of section 18 is designated MN 4-5.

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	
A																										A
B																										B
C		6			5			4				3			2					1						C
D																										D
E																										E
F																										F
G		7			8			9				10			11					12						G
H																										H
J																										J
K																										K
L		18			17			16				15			14					13						L
M																										M
N																										N
O																										O
P		19			20			21				22			23					24						P
Q																										Q
R																										R
S																										S
T		30			29			28				27			26					25						T
U																										U
V																										V
W																										W
X		31			32			33				34			35					36						X
Y																										Y
Z																										Z
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	

RCW 58.09.060 (2) requires the following information on this form: an accurate description and location, in reference to the corner position, of all monuments and accessories (a) found at the corner and (b) placed or replaced at the corner; (c) basis of bearings used to describe or locate such monuments or accessories; and (d) corollary information that may be helpful to relocate or identify the corner position.

SPACE FOR ADDITIONAL COMMENT: